

**BELLINZONI S.R.L.**

Revision nr. 8

Dated 13/02/2023

IDEA DARK

Printed on 13/02/2023

Page n. 1/19

Replaced revision:7 (Printed on: 09/12/2020)

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: 082CDARK - 082CDARK00250 - 082CDARK001 - 082CDARK005 - 082CDARK025 - 082CDARK200

Product name: **IDEA DARK**

UFI : 9AT0-80S8-3004-TH7Q

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: **Waterproofing and intensifying the color of marble, granite and stone**

Identified Uses	Industrial	Professional	Consumer
Waterproofing, color intensifier	ERC: 8c, 8f. PROC: 10, 7. AC: 4a. PC: 15. LCS: IS.	ERC: 8c, 8f. PROC: 10, 11. AC: 4a. PC: 15. LCS: PW.	-

1.3. Details of the supplier of the safety data sheet

Name: **BELLINZONI S.R.L.**

Full address: **Via Mezzano 64**

District and Country: **28069 Trecate (NO) Italia**

Tel. **+39 0321 770558**

e-mail address of the competent person

responsible for the Safety Data Sheet

Supplier:

laboratorio@bellinzoni.com
BELLINZONI S.r.l.

1.4. Emergency telephone number

For urgent inquiries refer to

- CAV "Osp. Pediatrico Bambino Gesù" Dip. Emergenza e Accettazione DEA – Roma - Piazza Sant'Onofrio, 4 CAP: 00165 – Telefono: 06 68593726 – Responsabile: Marco Marano
- Az. Osp. Univ. Foggia – Foggia - V.le Luigi Pinto, 1 – CAP: 71122 – Telefono: 800183459 – Responsabile: Anna Lepore
- Az. Osp. "A. Cardarelli" – Napoli - Via A. Cardarelli, 9 – CAP: 80131081- Telefono: 5453333 – Responsabile: Romolo Villani
- CAV Policlinico "Umberto I" - Roma - V.le del Policlinico, 155 – CAP: 161 – Telefono: 06-49978000 – Responsabile: M. Caterina Grassi
- CAV Policlinico "A. Gemelli" - Roma - Largo Agostino Gemelli, 8 – CAP: 168 – Telefono: 06-3054343 – Responsabile: Alessandro Barelli
- Az. Osp. "Careggi" U.O. Tossicologia Medica – Firenze - Largo Brambilla, 3 – CAP: 50134 – Telefono: 055-7947819 – Responsabile: Francesco Gambassi
- CAV Centro Nazionale di Informazione Tossicologica - Pavia – Via Salvatore Maugeri, 10 – CAP: 27100 - Telefono: 0382-24444 – Responsabile: Carlo Locatelli
- Osp. Niguarda Ca' Granda – Milano - Piazza Ospedale Maggiore, 3 – CAP: 20162 – Telefono: 02-66101029 – Responsabile: Franca Davanzo
- Azienda Ospedaliera Papa Giovanni XXII – Bergamo - Piazza OMS, 1 – CAP: 24127 – Telefono: 800883300 – Responsabile: Bacis Giuseppe
- Azienda Ospedaliera Integrata Verona – Verona - Piazzale Aristide Stefani, 1 – CAP: 37126 – Telefono 800011858

	BELLINZONI S.R.L.	Revision nr. 8
	IDEA DARK	Dated 13/02/2023 Printed on 13/02/2023 Page n. 2/19 Replaced revision:7 (Printed on: 09/12/2020)

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Flammable liquid, category 3	H226	Flammable liquid and vapour.
Aspiration hazard, category 1	H304	May be fatal if swallowed and enters airways.
Specific target organ toxicity - single exposure, category 3	H336	May cause drowsiness or dizziness.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: Danger

Hazard statements:

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH210	Safety data sheet available on request.

Precautionary statements:

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing dust / fume / gas / mist / vapours / spray.
P280	Wear protective gloves/ protective clothing / eye protection / face protection.
P301+P310	IF SWALLOWED: immediately call a POISON CENTER / doctor
P331	Do NOT induce vomiting.
P501	Dispose of the product / container in accordance with local / regional / national / international regulations.

Contains: HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage $\geq$ than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration $\geq$ 0.1%.

	BELLINZONI S.R.L.	Revision nr. 8
	IDEA DARK	Dated 13/02/2023 Printed on 13/02/2023 Page n. 3/19 Replaced revision:7 (Printed on: 09/12/2020)

SECTION 3. Composition/information on ingredients

3.1. Substances

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS INDEX - EC 919-857-5 CAS - REACH Reg. 01-2119463258-33	60 ≤ x < 65	Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 H336, EUH066 Classification note according to Annex VI of the CLP Regulation: H, P
ETHYL SILICATE INDEX 014-005-00-0 EC 201-083-8 CAS 78-10-4 REACH Reg. 01-2119496195-28	0,4 ≤ x < 0,55	Flam. Liq. 3 H226, Acute Tox. 4 H332, Eye Irrit. 2 H319, STOT SE 3 H335 LC50 Inhalation vapours: 10 mg/l/4h
TOLUENE INDEX 601-021-00-3 EC 203-625-9 CAS 108-88-3 REACH Reg. 01-2119471310-51	0,25 ≤ x < 0,4	Flam. Liq. 2 H225, Repr. 2 H361d, Asp. Tox. 1 H304, STOT RE 2 H373, Skin Irrit. 2 H315, STOT SE 3 H336

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

	BELLINZONI S.R.L.	Revision nr. 8
	IDEA DARK	Dated 13/02/2023 Printed on 13/02/2023 Page n. 4/19 Replaced revision:7 (Printed on: 09/12/2020)

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

	BELLINZONI S.R.L.	Revision nr. 8
	IDEA DARK	Dated 13/02/2023 Printed on 13/02/2023 Page n. 5/19 Replaced revision:7 (Printed on: 09/12/2020)

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.

ETHYL SILICATE

Keep away from sources of ignition - No smoking

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

ETHYL SILICATE

Keep the container in a cool and well-ventilated place. Protect from ultraviolet irradiation / sunlight
Humidity. Use only in well-ventilated areas.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

AUS	Österreich	Gesamte Rechtsvorschrift für Grenzwerteverordnung 2021 , Fassung vom 17.06.2021
BEL	Belgique	Liste de valeurs limites d'exposition aux agents chimiques, livre VI du code du bien-être au travail
BGR	България	НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г. ЗА ЗАЩИТА НА РАБОТЕЩИТЕ ОТ РИСКОВЕ, СВЪРЗАНИ С ЕКСПОЗИЦИЯ НА ХИМИЧНИ АГЕНТИ ПРИ РАБОТА (изм. ДВ. бр.5 от 17 Януари 2020г.)
CHE	Suisse / Schweiz	Valeurs limites d'exposition aux postes de travail: VME/VLE (SUVA). Grenzwerte am Arbeitsplatz: MAK (SUVA)
CYP	Κύπρος	Οι περί Αζθάλειας και Υγείας στην Εργασία (Καρκινογόνοι και Μεταλλαξιογόνοι Παράγοντες) (Τροποποιητικοί) Κανονισμοί του 2020
CZE	Česká Republika	Nařízení vlády č. 41/2020 Sb. Nařízení vlády, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci, ve znění pozdějších předpisů
DEU	Deutschland	Technischen Regeln für Gefahrstoffe (TRGS 900) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte. MAK- und BAT-Werte-Liste 2020, Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe, Mitteilung 56
DNK	Danmark	Bekendtgørelse om grænseværdier for stoffer og materialer - BEK nr 1458 af 13/12/2019
ESP	España	Límites de exposición profesional para agentes químicos en España 2021
EST	Eesti	Ohtlike kemikaalide ja neid sisaldavate materjalide kasutamise töötervishoiu ja tööohutuse nõuded ning töökeskkonna keemiliste ohutegurite piirnormid [RT I, 17.10.2019, 1 - jõust. 17.01.2020]
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
FIN	Suomi	HTP-VÄRDEN 2020. Koncentrationer som befunnits skadliga. SOCIAL - OCH HÄLSOVÄRDSMINISTERIETS PUBLIKATIONER 2020:25
GRC	Ελλάδα	Π.Δ. 26/2020 (ΦΕΚ 50/Α' 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ ``σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξιογόνους παράγοντες κατά την εργασία``»
HUN	Magyarország	Az innovációért és technológiáért felelős miniszter 5/2020. (II. 6.) ITM rendelete a kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelmére

	BELLINZONI S.R.L.		Revision nr. 8
			Dated 13/02/2023
	IDEA DARK		Printed on 13/02/2023 Page n. 6/19 Replaced revision:7 (Printed on: 09/12/2020)

HRV	Hrvatska	Pravilnik o izmjenama i dopunama Pravilnika o zaštiti radnika od izloženosti opasnim kemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 1/2021)
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
IRL	Éire	2020 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations (2001-2015) and the Safety, Health and Welfare at Work (Carcinogens) Regulations (2001-2019)
LUX	Luxembourg	Règlement grand-ducal du 24 janvier 2020 modifiant le règlement grand-ducal du 14 novembre 2016 concernant la protection des salariés contre les risques liés à l'exposition à des agents cancérigènes ou mutagènes au travail
LTU	Lietuva	Jsakymas dėl lietuvs higienos normos hn 23:2011 „cheminių medžiagų profesinio poveikio ribiniai dydžiai. Matavimo ir poveikio vertinimo bendrieji reikalavimai“ patvirtinimo
LVA	Latvija	Grozījumi Ministru kabineta 2007. gada 15. maija noteikumos Nr. 325 "Darba aizsardzības prasības saskarē ar ķīmiskajām vielām darba vietās" (prot. Nr. 32 18. §; prot. Nr. 1 22. §)
MLT	Malta	PROTECTION OF THE HEALTH AND SAFETY OF WORKERS FROM THE RISKS RELATED TO CHEMICAL AGENTS AT WORK REGULATIONS (S.L.424.24). PROTECTION OF WORKERS FROM THE RISKS RELATED TO EXPOSURE TO CARCINOGENS OR MUTAGENS AT WORK REGULATIONS (S.L.424.22)
NOR	Norge	Forskrift om endring i forskrift om tiltaksverdi og grenseverdi for fysiske og kjemiske faktorer i arbeidsmiljøet samt smitterisikogrupper for biologiske faktorer (forskrift om tiltaks- og grenseverdi), 21. august 2018 nr. 1255
NLD	Nederland	Arbeidsomstandighedenregeling. Lijst van wettelijke grenswaarden op grond van de artikelen 4.3, eerste lid, en 4.16, eerste lid, van het Arbeidsomstandighedenbesluit
PRT	Portugal	Decreto-Lei n.º 1/2021 de 6 de janeiro, valores-limite de exposição profissional indicativos para os agentes químicos. Decreto-Lei n.º 35/2020 de 13 de julho, proteção dos trabalhadores contra os riscos ligados à exposição durante o trabalho a agentes cancerígenos ou mutagénicos
POL	Polska	Rozporządzenie ministra rozwoju, pracy i technologii z dnia 18 lutego 2021 r. Zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w środowisku pracy
ROU	România	Hotărârea nr. 53/2021 pentru modificarea hotărârii guvernului nr. 1.218/2006, precum și pentru modificarea și completarea hotărârii guvernului nr. 1.093/2006
SWE	Sverige	Hygieniska gränsvärden, Arbetsmiljöverkets föreskrifter och allmänna råd om hygieniska gränsvärden (AFS 2018:1)
SVK	Slovensko	NARIADENIE VLÁDY Slovenskej republiky z 12. augusta 2020, ktorým sa mení a dopĺňa nariadenie vlády Slovenskej republiky č. 356/2006 Z. z. o ochrane zdravia zamestnancov pred rizikami súvisiacimi s expozíciou karcinogénnym a mutagénnym faktorom pri práci v znení neskorších predpisov
SVN	Slovenija	Pravilnik o varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu (Uradni list RS, št. 100/01, 39/05, 53/07, 102/10, 43/11 – ZVZD-1, 38/15, 78/18 in 78/19)
TUR	Türkiye	Kimyasal Maddelerle Çalışmalarda Sağlık ve Güvenlik Önlemleri Hakkında Yönetmelik 12.08.2013 / 28733
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
EU	OEL EU	Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2022

HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS								
Threshold Limit Value								
Type	Country	TWA/8h		STEL/15min		Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			
AGW	DEU	300	50	600	100			
NDS/NDSch	POL	300		900				
TLV-ACGIH		1200	197	0	0			
Health - Derived no-effect level - DNEL / DMEL								
	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	300 mg/kg bw/d				
Inhalation			VND	900 mg/m3		VND		1500 mg/m3
Skin			VND	300 mg/kg bw/d		VND		300 mg/kg bw/d

ETHYL SILICATE						
Threshold Limit Value						
Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
MAK	AUS	44	5	88	10	STEL:5(Mow), Häufigkeit/Sch:8x
VLEP	BEL	44	5			
TLV	BGR	44	5			
MAK	CHE	85	10	85	10	
VME/VLE	CHE	85	10	85	10	
TLV	CYP	44	5			
TLV	CZE	50	5,85	200	23,4	
AGW	DEU	12	1,4	12 (C)	1,4 (C)	
MAK	DEU	86	10	86	10	
TLV	DNK	85	10			
VLEP	FRA	85	10			
HTP	FIN	43	5	86	10	
TLV	GRC	44	5			
AK	HUN	44				
GVI/KGVI	HRV	44	5			
VLEP	ITA	44	5			
OELV	IRL	44	5			
VL	LUX	44	5			
RD	LTU	44	5			
RV	LVA	44	5			
TLV	MLT	44	5			
TLV	NOR	44	5			
TGG	NLD	44				
VLE	PRT	44	5			
NDS/NDSch	POL	44				
TLV	ROU	44	5			
NPEL	SVK	44	5			
MV	SVN	170	20	170	20	
WEL	GBR	44	5			
OEL	EU	44	5			
TLV-ACGIH		85	10			
Predicted no-effect concentration - PNEC						
Normal value in fresh water				0,192	mg/l	
Normal value in marine water				0,0192	mg/l	
Normal value for fresh water sediment				0,18	mg/kg	
Normal value for marine water sediment				0,018	mg/kg	

	BELLINZONI S.R.L.					Revision nr. 8		
	IDEA DARK					Dated 13/02/2023		
						Printed on 13/02/2023		
					Page n. 8/19			
					Replaced revision:7 (Printed on: 09/12/2020)			
Normal value for water, intermittent release				10		mg/l		
Normal value of STP microorganisms				4000		mg/l		
Normal value for the terrestrial compartment				0,05		mg/kg		
Health - Derived no-effect level - DNEL / DMEL								
	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation	25 mg/m3	25 mg/m3	25 mg/m3	25 mg/m3	85 mg/m3	85 mg/m3	85 mg/m3	85 mg/m3
Skin	VND	8,4 mg/kg/d	VND	8,4 mg/kg/d		VND	VND	
TOLUENE								
Threshold Limit Value								
Type	Country	TWA/8h		STEL/15min		Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm			
MAK	AUS	190	50	380	100	SKIN	Häufigkeit pro Schicht:4x	
VLEP	BEL	77	20	384	100	SKIN		
TLV	BGR	192	50	384	100	SKIN		
MAK	CHE	190	50	760	200	SKIN		
VME/VLE	CHE	190	50	760	200	SKIN		
TLV	CZE	192	50,112	384	100,224	SKIN		
AGW	DEU	190	50	760	200	SKIN		
MAK	DEU	190	50	760	200	SKIN		
TLV	DNK	94	25			SKIN	E	
VLA	ESP	192	50	384	100	SKIN		
TLV	EST	192	50	384	100	SKIN		
VLEP	FRA	76,8	20	384	100	SKIN		
HTP	FIN	81	25	380	100	SKIN	Buller	
TLV	GRC	192	50	384	100			
AK	HUN	190		380		SKIN		
GVI/KGVI	HRV	192	50	384	100	SKIN		
VLEP	ITA	192	50			SKIN		
OELV	IRL	192	50	384	100	SKIN		
VL	LUX	192	50	384	100	SKIN		
RD	LTU	192	50	384	100	SKIN		
RV	LVA	50	14	150	40	SKIN		
TLV	MLT	192	50	384	100	SKIN		
TLV	NOR	94	25			SKIN		
TGG	NLD	150		384				
VLE	PRT	192	50	384	100	SKIN		
NDS/NDSch	POL	100		200		SKIN		
TLV	ROU	192	50	384	100	SKIN		
NGV/KGV	SWE	192	50	384	100	SKIN		
NPEL	SVK	192	50	384	100	SKIN		
MV	SVN	192	50	384	100	SKIN		

	BELLINZONI S.R.L.					Revision nr. 8
	IDEA DARK					Dated 13/02/2023 Printed on 13/02/2023 Page n. 9/19 Replaced revision:7 (Printed on: 09/12/2020)

ESD	TUR	192	50	384	100	SKIN
WEL	GBR	191	50	384	100	SKIN
OEL	EU	192	50	384	100	SKIN
TLV-ACGIH		75,4	20			

Predicted no-effect concentration - PNEC						
Normal value in fresh water				0,68	mg/l	
Normal value in marine water				0,68	mg/l	
Normal value for fresh water sediment				16,39	mg/kg/d	
Normal value for marine water sediment				16,39	mg/kg/d	
Normal value for water, intermittent release				0,68	mg/l	
Normal value of STP microorganisms				13,61	mg/l	
Normal value for the terrestrial compartment				2,89	mg/kg	

Health - Derived no-effect level - DNEL / DMEL								
Effects on consumers				Effects on workers				
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	8,13 mg/kg bw/d				
Inhalation	226 mg/m3	226 mg/m3	56,6 mg/m3	56,5 mg/m3	384 mg/m3	384 mg/m3	192 mg/m3	192 mg/m3
Skin			VND	226 mg/kg bw/d			VND	384 mg/kg bw/d

Legend:
(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.
VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

HAND PROTECTION

The use of fluororubber gloves is recommended, minimum thickness 0.71 mm, breakthrough time ≥ 480 minutes according to CEN, EN420 and EN 374 standards. The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

	BELLINZONI S.R.L.	Revision nr. 8
	IDEA DARK	Dated 13/02/2023 Printed on 13/02/2023 Page n. 10/19 Replaced revision:7 (Printed on: 09/12/2020)

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	liquid	Method:visual
Colour	colourless	
Odour	solvent	
Melting point / freezing point	< -20 °C	Remark:EC Regulation 1907/2006, Annex VII
Initial boiling point	154 °C	Substance:HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS
Flammability	flammable liquid	
Lower explosive limit	not available	Concentration: 0,7 % Substance:HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS
Upper explosive limit	not available	Concentration: 6 % Substance:HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS
Flash point	> 41 °C	Substance:HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS
Auto-ignition temperature	237 °C	Substance:HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS
Decomposition temperature	not available	
pH	not applicable	Reason for missing data:the mixture is not polar / aprotic
Kinematic viscosity	94 mm ² /s	Method:Calculation
Dynamic viscosity	80 mPa s	
Solubility	insoluble in water	
Partition coefficient: n-octanol/water	> 4	Substance:HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS
Vapour pressure	30,89 hPa	Substance:TOLUENE
Density and/or relative density	0,85 g/l	Method:Own Instrument: METTLER TOLEDO DENSITOPRO
Relative vapour density	not available	
Particle characteristics	not applicable	

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

VOC (Directive 2010/75/EU)	63,34 % - 541,63 g/litre	
VOC (volatile carbon)	53,66 % - 458,83 g/litre	
Explosive properties	not explosive	Remark:it does not contain substances classified as explosive
Oxidising properties	not oxidizing	Remark:it does not contain substances classified as oxidizing

	BELLINZONI S.R.L.	Revision nr. 8
	IDEA DARK	Dated 13/02/2023 Printed on 13/02/2023 Page n. 11/19 Replaced revision:7 (Printed on: 09/12/2020)

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

ETHYL SILICATE

Vapors can form an explosive mixture with air. Reacts with water

TOLUENE

Avoid exposure to: light.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

ETHYL SILICATE

Can react violently with oxidizing agents and strong acids. Reaction with alkali metals. Reaction with alkaline earth metals.

TOLUENE

Risk of explosion on contact with: fuming sulphuric acid,nitric acid,silver perchlorate,nitrogen dioxide,non-metal halogenates,acetic acid,organic nitrocompounds.May form explosive mixtures with: air.May react dangerously with: strong oxidising agents,strong acids,sulphur.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

ETHYL SILICATE

Avoid the accumulation of electrostatic charges. Keep away from heat (eg hot surfaces), sparks and open flames. To protect from humidity and water.

10.5. Incompatible materials

ETHYL SILICATE

Oxidizing agents. Acids. Alkalis. Water.

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

ETHYL SILICATE

Flammable Can be released in case of fire: Carbon oxides. Ethanol

	BELLINZONI S.R.L.	Revision nr. 8
	IDEA DARK	Dated 13/02/2023 Printed on 13/02/2023 Page n. 12/19 Replaced revision:7 (Printed on: 09/12/2020)

SECTION 11. Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

TOLUENE

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of ambient air; contact with the skin of products containing the substance.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

TOLUENE

Toxic effect on the central and peripheral nervous system with encephalopathy and polyneuritis; irritating for the skin, conjunctiva, cornea and respiratory apparatus.

Interactive effects

TOLUENE

Certain drugs and other industrial products can interfere with the metabolism of the toluene.

ACUTE TOXICITY

ATE (Inhalation) of the mixture:	Not classified (no significant component)
ATE (Oral) of the mixture:	Not classified (no significant component)
ATE (Dermal) of the mixture:	Not classified (no significant component)

HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

LD50 (Dermal):	> 3160 mg/kg Rabbit, m/f
LD50 (Oral):	> 5000 mg/kg Rat, m/f
LC50 (Inhalation vapours):	> 4951 mg/m ³ Rat

ETHYL SILICATE

LD50 (Oral):	> 10 mg/kg/4h rat
LC50 (Inhalation vapours):	10 mg/l/4h

TOLUENE

LD50 (Dermal):	12267 mg/kg Rabbit
LD50 (Oral):	5580 mg/kg Rat
LC50 (Inhalation vapours):	25,7 mg/l/4h Rat

SKIN CORROSION / IRRITATION

Repeated exposure may cause skin dryness or cracking.

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

	BELLINZONI S.R.L.	Revision nr. 8
	IDEA DARK	Dated 13/02/2023 Printed on 13/02/2023 Page n. 13/19 Replaced revision:7 (Printed on: 09/12/2020)

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

TOLUENE

Classified in Group 3 (not classifiable as a human carcinogen) by the International Agency for Research on Cancer (IARC) - (IARC, 1999).
The US Environmental Protection Agency (EPA) affirms that "the data is inadequate for an assessment of the carcinogenic potential".

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

May cause drowsiness or dizziness

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Toxic for aspiration

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

TOLUENE

LC50 - for Fish

5,5 mg/l/96h

EC50 - for Algae / Aquatic Plants

3,78 mg/l/72h

	BELLINZONI S.R.L.		Revision nr. 8
	IDEA DARK		Dated 13/02/2023 Printed on 13/02/2023 Page n. 14/19 Replaced revision:7 (Printed on: 09/12/2020)

ETHYL SILICATE	
LC50 - for Fish	245 mg/l/96h danio rerio
EC50 - for Crustacea	> 75 mg/l/48h daphnia magna
EC50 - for Algae / Aquatic Plants	> 22 mg/l/72h pseudokirchneriella subcapitata
HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS	
LC50 - for Fish	> 1000 mg/l/96h oncorhynchus mykiss
EC50 - for Crustacea	> 1000 mg/l/48h daphnia magna
EC50 - for Algae / Aquatic Plants	> 1000 mg/l/72h pseudokirchneriella subcapitata

12.2. Persistence and degradability

TOLUENE	
Solubility in water	100 - 1000 mg/l
Rapidly degradable	
ETHYL SILICATE	
Solubility in water	1000 - 10000 mg/l
Rapidly degradable	
HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS	
Rapidly degradable	

12.3. Bioaccumulative potential

TOLUENE	
Partition coefficient: n-octanol/water	2,73
BCF	90
ETHYL SILICATE	
Partition coefficient: n-octanol/water	3,18
BCF	3,16
HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS	
Partition coefficient: n-octanol/water	5,85

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage $\geq$ than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

	BELLINZONI S.R.L.	Revision nr. 8
	IDEA DARK	Dated 13/02/2023 Printed on 13/02/2023 Page n. 15/19 Replaced revision:7 (Printed on: 09/12/2020)

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

14.1. UN number or ID number

ADR / RID, IMDG, IATA: 1263

14.2. UN proper shipping name

ADR / RID: PAINT or PAINT RELATED MATERIAL

IMDG: PAINT or PAINT RELATED MATERIAL

IATA: PAINT or PAINT RELATED MATERIAL

14.3. Transport hazard class(es)

ADR / RID: Class: 3 Label: 3

IMDG: Class: 3 Label: 3

IATA: Class: 3 Label: 3



14.4. Packing group

ADR / RID, IMDG, IATA: III

14.5. Environmental hazards

ADR / RID: NO

IMDG: NO

IATA: NO

	BELLINZONI S.R.L.	Revision nr. 8
	IDEA DARK	Dated 13/02/2023 Printed on 13/02/2023 Page n. 16/19 Replaced revision:7 (Printed on: 09/12/2020)

14.6. Special precautions for user

ADR / RID:	HIN - Kemler: 30	Limited Quantities: 5 L	Tunnel restriction code: (D/E)
IMDG:	Special provision: - EMS: F-E, <u>S-E</u>	Limited Quantities: 5 L	
IATA:	Cargo:	Maximum quantity: 220 L	Packaging instructions: 366
	Passengers:	Maximum quantity: 60 L	Packaging instructions: 355
	Special provision:	A3, A72, A192	

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: P5c

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product
Point 3 - 40

Contained substance

Point 75

Point 48 TOLUENE REACH Reg.: 01-2119471310-51

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage $\geq$ than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

	BELLINZONI S.R.L.	Revision nr. 8
	IDEA DARK	Dated 13/02/2023 Printed on 13/02/2023 Page n. 17/19 Replaced revision:7 (Printed on: 09/12/2020)

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 2	Flammable liquid, category 2
Flam. Liq. 3	Flammable liquid, category 3
Repr. 2	Reproductive toxicity, category 2
Acute Tox. 4	Acute toxicity, category 4
Asp. Tox. 1	Aspiration hazard, category 1
STOT RE 2	Specific target organ toxicity - repeated exposure, category 2
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H361d	Suspected of damaging the unborn child.
H332	Harmful if inhaled.
H304	May be fatal if swallowed and enters airways.
H373	May cause damage to organs through prolonged or repeated exposure.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH210	Safety data sheet available on request.

	BELLINZONI S.R.L.	Revision nr. 8
	IDEA DARK	Dated 13/02/2023 Printed on 13/02/2023 Page n. 18/19 Replaced revision:7 (Printed on: 09/12/2020)

Use descriptor system:

AC	4a	Stone, plaster, cement, glass and ceramic articles: Large surface area articles
ERC	8c	Widespread use leading to inclusion into/onto article (indoor)
ERC	8f	Widespread use leading to inclusion into/onto article (outdoor)
LCS	IS	Use at industrial sites
LCS	PW	Widespread use by professional workers
PC	15	Non-metal-surface treatment products
PROC	10	Roller application or brushing
PROC	11	Non industrial spraying
PROC	7	Industrial spraying

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)

	BELLINZONI S.R.L.	Revision nr. 8
	IDEA DARK	Dated 13/02/2023 Printed on 13/02/2023 Page n. 19/19 Replaced revision:7 (Printed on: 09/12/2020)

17. Regulation (EU) 2019/1148
18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:

The following sections were modified:

01 / 02 / 03 / 07 / 08 / 09 / 10 / 11 / 12 / 15 / 16.