

TECHNICAL DATA SHEET (TDS)

IDEA QUARZO

ID Product Code 088

Pag | 1

COLOR ENHANCER PROTECTIVE AGENT

Quartz Impregnating enhancer with darkening action.



Product description:

Ready to use impregnating protective agent, solvent based, suitable for protective treatment of quartz surfaces.

IDEA QUARZO intensifies the natural color of material, has good penetration, does not form a film on the surface. It does not turn yellow, is perfect for treating indoor or outdoor surfaces, it is water and dirt resistant. Tests carried out in laboratories demonstrate resistance to UV rays. The treated stone does not change its color after long exposure to UV rays. It prevents formation of mildew. It can be used for treatment of quartz-resin agglomerates. It is the suitable product to treat kitchen and vanity top.

Chemical characteristics:

Appearance	Liquid
Color	Clear transparent
Odor	Characteristic
Specific gravity at 20° C (68° F)	0,85±0,02
Hydro-solubility	Not soluble
pH	N.A.
Drying time at 20°C (68° F)	45-60 minutes*
Complete drying time	8 hours*
U.V. Resistance:	
Long waves 365 nm	Very good (no changes after 24 hours exposure)
Short waves 254 nm	Very good (no changes after 24 hours exposure)
Shelf life at 20°C (68° F)	24 months in original container

* indicative values, depending on the nature of the material and environmental conditions

Instruction for use

Surface must be clean, dry, without any trace of dirt; stone to be treated must not contain salts (sulfates, chlorides and nitrates) since their presence reduces the absorption. Stains, mildew, crusting must be scraped off otherwise they will be harder to remove after protection. Apply IDEA QUARZO without any dilution, using a cotton or microfiber cloth. Apply necessary quantity up to complete absorption. After 10/15 minutes, remove excess of product with an absorbing cloth. The product can also be applied on the production line.

During application and subsequent drying, temperature of the substrate should be between 10 and 30°C. In case of application on floor with underfloor heating system turn off heating and allow the stone to cool completely.

Application tools



Brush



Roll



Cloth



Fleece



DISCLAIMER All data indicated in this leaflet are the results of tests and experiments carried out in our laboratories and through reliable operators in the stone business and have to be considered reliable. Because of the many factors which can influence them, the information here reported do not constitute implicit or formal guarantees. The end user undertakes the responsibility in the usage of the product making sure to experiment the product characteristic as preventive measure.



TDS N°
088

TECHNICAL DATA SHEET (TDS)

Suggestion for use and recommendations:

- Do not dilute the product with water or other solvents because the preparation is ready for use.
- The material to be treated must be completely dry.
- Once treated, the surface must be left to dry for 12 hours to complete polymerization.
- In the case of floor treatments wait 12 hours before walking.
- Before use carefully read the recommendations printed on the tin
- Make a test before use

Pag | 2

Application surfaces

Engineered stones quartz based, polished, unpolished, flamed, rough or bush-hammered.

Coverage

For the treatment of polished quartz, one liter of product can treat around 50 sqm (540 sq.ft.) of material.

Maintenance of the treated surface

For proper maintenance of treatment (floors) we recommend to carry out periodic washing with our LEM-3 neutral detergent, diluted with water according to the amount of dirt to be removed, without using abrasive tools. The treatment has a variable duration, depending on weather condition it is exposed to and wear of the material. If necessary, it is possible to reapply IDEA QUARZO above a previous application.

For maintenance of kitchen and vanity top it is suggested to use Bellinzoni QUARTZ CARE SYSTEM.

Safety procedures

As far as the proper working procedures is concerned, we recommend to consult Material Safety Data Sheets issued according to E.U. rules and to follow your national laws concerning safety in the working place. MSDS is available on our web site www.bellinzoni.com

Packing

Item N°	Packing	Pcs
088CQZ000250	250 ml (8,5 fl.oz.)	12
088CQZ001	1,00 lt (33,82 fl.oz.)	6
088CQZ005	5,00 lt (1,32 Gal)	2
088CQZ025	25,00 lt (6,60 Gal)	1

The composition of the tins is Steel (ACC). After use, comply with the local and national regulations currently in force regarding recycling. Our packing is conformed as per U.N. rules for inland transport (A.D.R.) and by sea (I.M.O.) for transportation via air refer to updated rules (I.A.T.A.). For further information regarding transport please check MSDS.

Trademark and Origin of the good

BELLINZONI® is a registered trademark of Bellinzoni company. The law considers a trademark to be a form of property and any misuse can be persecuted by law. Bellinzoni s.r.l. declares that our product IDEA QUARZO is **MADE IN ITALY**.



DISCLAIMER All data indicated in this leaflet are the results of tests and experiments carried out in our laboratories and through reliable operators in the stone business and have to be considered reliable. Because of the many factors which can influence them, the information here reported do not constitute implicit or formal guarantees. The end user undertakes the responsibility in the usage of the product making sure to experiment the product characteristic as preventive measure.



TDS N°
088