

Goliath Steel Toe (8968200)

Polyblend® compound and a sleek design gives you chemical protection and all day comfort



USP Outsole

Power lug outsole powered by a multi tread design provides exceptional comfort and slip resistance

USP Shaft

Polyblend compound offers superior resistance to fats, oils and chemicals

USP Safety

Steel toe complies with ASTM F2413-11 with steel shank

General

Segment	Food
Material boot shaft	PVC
Material outsole	PVC
Color shaft	Black
Color outsole	Grey
Insole type	Standard insole

Certification

Safety standard USA	ASTM F2413-11 M I/75 C/75 SD + ASTM F3445-21 SR
---------------------	--

Protection & Comfort

Toe cap	Steel
Oil resistant outsole	Yes
Energy absorbing	Yes
Electrical insulation	Antistatic
Fuel oil resistant	Yes

Sizing

Size range US	05-15
---------------	-------

Logistics

Country of origin	United States of America
Intrastat code	64011000

SKU	Size EUR	Size US	Size UK	GTIN	Prs/Outer pack	Outer pack length (mm)	Outer pack width (mm)	Outer pack height (mm)	Prs/Pallet	Pallet height (mm)
8968200.05		05		791079150580	6	542.925	469.9	314.325	132	1880.7875
8968200.06		06		791079150597	6	542.925	469.9	314.325	132	1880.7875
8968200.07		07		791079150603	6	542.925	469.9	314.325	132	1880.7875
8968200.08		08		791079150610	6	542.925	469.9	314.325	132	1880.7875
8968200.09		09		791079150627	6	542.925	469.9	314.325	132	1880.7875
8968200.10		10		791079150634	6	542.925	469.9	314.325	132	1880.7875
8968200.11		11		791079150641	6	542.925	469.9	314.325	132	1880.7875
8968200.12		12		791079150658	6	542.925	469.9	314.325	132	1880.7875
8968200.13		13		791079150665	6	542.925	469.9	314.325	132	1880.7875
8968200.14		14		791079150672	6	542.925	469.9	314.325	132	1880.7875
8968200.15		15		791079150689	6	542.925	469.9	314.325	132	1880.7875

Creation date: April 22, 2025

PROTECTION AND COMFORT YOU DESERVE