

Revision nr. 2

Dated 06/06/2023

Printed on 06/06/2023

Page n. 1/25

Replaced revision:1 (Printed on: 09/09/2022)

B-LEM3 EXXTRA MG

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: P020LXMG - P020LXMG10L - P020LXMG50L

Product name B-LEM3 EXXTRA MG
UFI: DAW0-Y0X4-T00F-XFMY

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Concentrated neutral detergent for ordinary cleaning of surfaces in marble, granite, concrete, agglomerates,

natural stones

Identified Uses	Industrial	Professional	Consumer
Detergent for floors and washable surfaces	-	ERC: 8a. 8d.	ERC: 8a, 8d.
2 otorgon for moore and macriable carracte		PROC: 10, 8a.	PC: 35.
		PC: 35.	LCS: C.
		LCS: PW.	

1.3. Details of the supplier of the safety data sheet

Name
Full address
District and Country

Name
BELLINZONI S.R.L.
Via Mezzano 64
28069 Trecate (NO)
Italia

Tel. +39 0321 770558

e-mail address of the competent person

responsible for the Safety Data Sheet

Supplier:

laboratorio@bellinzoni.com

BELLINZONI S.r.I.

1.4. Emergency telephone number

For urgent inquiries refer to

- CAV "Osp. Pediatrico Bambino Gesù" Dip. Emergenza e Accettazione DEA Roma - Piazza Sant`Onofrio, 4 CAP: 00165 – Telefono: 06 68593726 – Responsabile: Marco Marano
- Az. Osp. Univ. Foggia Foggia V.le Luigi Pinto, 1 CAP: 71122 Telefono: 800183459 Responsabile: Anna Lepore
- Az. Osp. "A. Cardarelli" Napoli Via A. Cardarelli, 9 CAP: 80131081-Telefono: 5453333 – Responsabile: Romolo Villani
- CAV Policlinico "Umberto I" Roma V.le del Policlinico, 155 CAP: 161 Telefono: 06-49978000 – Responsabile: M. Caterina Grassi
- CAV Policlinico "A. Gemelli" Roma Largo Agostino Gemelli, 8 CAP: 168 -Telefono: 06-3054343 - Responsabile: Alessandro Barelli
- Az. Osp. "Careggi" U.O. Tossicologia Medica Firenze Largo Brambilla, 3 CAP: 50134 – Telefono: 055-7947819 – Responsabile: Francesco Gambassi
- CAV Centro Nazionale di Informazione Tossicologica Pavia Via Salvatore Maugeri, 10 – CAP: 27100 - Telefono: 0382-24444 – Responsabile: Carlo Locatelli
- Osp. Niguarda Ca' Granda Milano Piazza Ospedale Maggiore,3 CAP: 20162 – Telefono: 02-66101029 – Responsabile: Franca Davanzo
- Azienda Ospedaliera Papa Giovanni XXII Bergamo Piazza OMS, 1 CAP: 24127 – Telefono: 800883300 – Responsabile: Bacis Giuseppe
- Azienda Ospedaliera Integrata Verona Verona Piazzale Aristide Stefani, 1 CAP: 37126 Telefono 800011858



Revision nr. 2

Dated 06/06/2023

Printed on 06/06/2023

Page n. 2/25

Replaced revision:1 (Printed on: 09/09/2022)

B-LEM3 EXXTRA MG

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Eye irritation, category 2 H319 Causes serious eye irritation.
Skin sensitization, category 1A H317 May cause an allergic skin reaction.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: Warning

Hazard statements:

H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
EUH210 Safety data sheet available on request.

Precautionary statements:

P102 Keep out of reach of children.

P280 Wear protective gloves / eye protection / face protection.

P302+P352 IF ON SKIN: wash with plenty of water

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice / attention.
P337+P313 If eye irritation persists: Get medical advice / attention.

P501 Dispose of the product / container in accordance with local / regional / national / international regulations.

Contains: 2-METHYL-2H-ISOTHIAZOL-3-ONE

Ingredients according to Regulation (EC) No. 648/2004

Less than 5% Anionic surfactants, Soap 5% or over but less than 15% Non-ionic surfactants

dye

Perfumes (Limonene, Linalool, Benzyl Salicilate, Citronellol)

Preservation agents: 2-methyl-2H-isothiazol-3-one, 1,2-benzisothiazol-3(2H)-one

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration ≥ 0.1%.



Revision nr. 2

Dated 06/06/2023 Printed on 06/06/2023

Page n. 3/25

Replaced revision:1 (Printed on: 09/09/2022)

B-LEM3 EXXTRA MG

SECTION 3. Composition/information on ingredients

3.1. Substances

Information not relevant

3.2. Mixtures

Contains:

Identification x = Conc. % Classification (EC) 1272/2008 (CLP)

ALCOHOLS, C12-14, ETHOXYLATED, SULFATES, SODIUM SALTS (< 2.5 EO)

INDEX - $2 \le x < 3$ Eye Dam. 1 H318, Skin Irrit. 2 H315, Aquatic Chronic 3 H412

EC 500-234-8 Eye Dam. 1 H318: ≥ 10%, Eye Irrit. 2 H319: ≥ 5%

CAS 68891-38-3

REACH Reg. 01-2119488639-16-

OXIRANE, 2-METHYL, POLYMER WITH OXIRANE, MONO (2-

PROPILEPTYL) ETHER INDEX $2 \le x < 3$ Eye Irrit. 2 H319

EC 944-523-0

CAS -

ALPHA -TRIDECYL- OMEGA -HYDROXY-, BRANCHED

POLEY (OXY-1,2-ETHANYL),

INDEX $1 \le x < 2$ Acute Tox. 4 H302, Eye Dam. 1 H318

EC 500-241-6 LD50 Oral: >300 mg/kg

CAS 69011-36-5

DIPROPYLENE GLYCOL MONOMETHYL ETHER

INDEX - $0.7 \le x < 0.85$ Substance with a community workplace exposure limit.

EC 252-104-2 CAS 34590-94-8

REACH Reg. 01-2119450011-60

2-METHYL-2H-ISOTHIAZOL-3-ONE

INDEX - $0,0015 \le x <$ Acute Tox. 2 H330, Acute Tox. 3 H301, Acute Tox. 3 H311, Skin Corr. 1B

H314, Eye Dam. 1 H318, Skin Sens. 1A H317, Aquatic Acute 1 H400 M=10,

Aquatic Chronic 1 H410 M=1, EUH071

EC 220-239-6 Skin Sens. 1A H317: ≥ 0,0015%

CAS 2682-20-4 LD50 Oral: 183 mg/kg, LD50 Dermal: 218 mg/kg, LC50 Inhalation

mists/powders: 0,11 mg/l/4h

REACH Reg. 01-2120764690-50

The full wording of hazard (H) phrases is given in section 16 of the sheet.



Revision nr. 2

Dated 06/06/2023

Printed on 06/06/2023

Page n 4/25

Replaced revision:1 (Printed on: 09/09/2022)

B-LEM3 EXXTRA MG

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray. UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS


Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.



Revision nr. 2

Dated 06/06/2023

Printed on 06/06/2023

Page n. 5/25

Replaced revision:1 (Printed on: 09/09/2022)

B-LEM3 EXXTRA MG

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

BGR	България	НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г. ЗА ЗАЩИТА НА РАБОТЕЩИТЕ ОТ РИСКОВЕ, СВЪРЗАНИ С ЕКСПОЗИЦИЯ НА ХИМИЧНИ АГЕНТИ ПРИ РАБОТА (изм. ДВ. бр.5 от 17 Януари 2020г.)
CZE	Česká Republika	Nařízení vlády č. 41/2020 Sb. Nařízení vlády, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci, ve znění pozdějších předpisů
DEU	Deutschland	Technischen Regeln für Gefahrstoffe (TRGS 900) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte. MAK- und BAT-Werte-Liste 2020, Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe, Mitteilung 56
ESP	España	Límites de exposición profesional para agentes químicos en España 2021
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
GRC	Ελλάδα	Π.Δ. 26/2020 (ΦΕΚ 50/Α` 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ ``σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξιγόνους παράγοντες κατά την εργασία``»
HUN	Magyarország	Az innovációért és technológiáért felelős miniszter 5/2020. (II. 6.) ITM rendelete a kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
LTU	Lietuva	Jsakymas dėl lietuvos higienos normos hn 23:2011 "cheminių medžiagų profesinio poveikio ribiniai dydžiai. Matavimo ir poveikio vertinimo bendrieji reikalavimai" patvirtinimo
NOR	Norge	Forskrift om endring i forskrift om tiltaksverdier og grenseverdier for fysiske og kjemiske faktorer i arbeidsmiljøet samt smitterisikogrupper for biologiske faktorer (forskrift om tiltaks- og grenseverdier), 21.



Slovenija

SVN

Route of exposure

BELLINZONI S.R.L.

Revision nr. 2

Dated 06/06/2023 Printed on 06/06/2023

Page n 6/25

Replaced revision:1 (Printed on: 09/09/2022)

B-LEM3 EXXTRA MG

august 2018 nr. 1255

NLD Nederland Arbeidsomstandighedenregeling. Lijst van wettelijke grenswaarden op grond van de artikelen 4.3, eerste

lid, en 4.16, eerste lid, van het Arbeidsomstandighedenbesluit

Decreto-Lei n.º 1/2021 de 6 de janeiro, valores-limite de exposição profissional indicativos para os agentes químicos. Decreto-Lei n.º 35/2020 de 13 de julho, proteção dos trabalhadores contra os riscos ligados à PRT Portugal

exposição durante o trabalho a agentes cancerígenos ou mutagénicos

POL Polska Rozporządzenie ministra rozwoju, pracy i technologii z dnia 18 lutego 2021 r. Zmieniające rozporządzenie

w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w

środowisku pracy

Hotărârea nr. 53/2021 pentru modificarea hotărârii guvernului nr. 1.218/2006, precum și pentru modificarea ROU România

și completarea hotărârii guvernului nr. 1.093/2006

SWF . Hygieniska gränsvärden. Arbetsmiljöverkets föreskrifter och allmänna råd om hygieniska gränsvärden (AFS Sverige

2018:1)

SVK NARIADENIE VLÁDY Slovenskej republiky z 12. augusta 2020, ktorým sa mení a dopĺňa nariadenie vlády Slovensko

Slovenskej republiky č. 356/2006 Z. z. o ochrane zdravia zamestnancov pred rizikami súvisiacimi s

expozíciou karcinogénnym a mutagénnym faktorom pri práci v znení neskorších predpisov

Pravilnik o varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu (Uradni list

RS, št. 100/01, 39/05, 53/07, 102/10, 43/11 – ZVZD-1, 38/15, 78/18 in 78/19)

United Kingdom GBR EH40/2005 Workplace exposure limits (Fourth Edition 2020) EU

Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; OEL EU

Directive (EU) 2017/2398; Directive (EÚ) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive

2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.

RCP TLV ACGIH TLVs and BEIs -

ALCOHOLS, C12-14, ETHOXYLATED, SULFATES, SODIUM SALTS (< 2.5 EO)

Acute local

Appendix H

Predicted no-effect concentra	ation - PNEC							
Normal value in fresh water				24	m	g/l		
Normal value in marine water	r			24	m	g/l		
Normal value for fresh water sediment			9168	mç	g/kg			
Normal value for marine water sediment		917	mç	g/kg				
Normal value for water, intermittent release			71	mç	g/l			
Normal value of STP microorganisms			10000	mç	g/l			
Normal value for the terrestric	al compartment			75	mç	g/kg		
Health - Derived no-effe	ect level - DNEL / I	DMEL						
	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				15 mg/kg/d		•		
Inhalation				52 mg/m3				175 mg/m3
Skin			0.079 mg/cm2	1650 mg/kg/d			0.132 mg/cm2	2750 mg/kg/
POLEY (OXY-1,2-ETHAN		DECYL- OMEGA	-HYDROXY-, B	RANCHED				
	auon - FINEC							
Normal value in fresh water				0,074	m	g/l		
Normal value in marine wate	r			0,0074	mį	g/l		
Normal value for fresh water	sediment			0,604	mç	g/kg dw		
Normal value for marine water	er sediment			0,0604	m	g/kg dw		
Normal value for water, intern	mittent release			0,015	m	g/l		
Normal value of STP microor	rganisms			1,4	mç	g/l		
Normal value for the terrestric	al compartment			0,1	mç	g/kg dw		
Health - Derived no-effe	Effects on	DMEL			Effects on workers			
	consumers				WUIKEIS			

Chronic

Acute local

Acute

Chronic local

Chronic

Acute systemic Chronic local



Revision nr. 2

Dated 06/06/2023

Printed on 06/06/2023

Page n. 7/25

Replaced revision:1 (Printed on: 09/09/2022)

B-LEM3 EXXTRA MG

	systemic	systemic	systemic
Oral	25 mg/kg		
	bw/d		
Inhalation	87 mg/m3		294 mg/m3
			<u>-</u>
Skin	1250 mg/kg		2080 mg/kg
	bw/d		bw/d

ONIT				bw/d				bw/d
DIPROPYLENE GLYCOL Threshold Limit Value	MONOMETHYL	_ ETHER						
Туре	Country	TWA/8h		STEL/15min		Remarks / Observation	s	
		mg/m3	ppm	mg/m3	ppm	020011441011		
TLV	BGR	308	50			SKIN		
TLV	CZE	270	47,34	550	89,1	SKIN		
AGW	DEU	310	50	310	50			
MAK	DEU	310	50	310	50			
VLA	ESP	308	50			SKIN		
VLEP	FRA	308	50			SKIN		
TLV	GRC	600	10	900	150			
AK	HUN	308						
VLEP	ITA	308	50			SKIN		
TLV	NOR	300	50			SKIN		
TGG	NLD	300				Sitily		
VLE	PRT	308	50			CIZINI		
			50			SKIN		
NDS/NDSCh	POL	240		480		SKIN		
TLV	ROU	308	50			SKIN		
NGV/KGV	SWE	300	50	450 (C)	75 (C)	SKIN		
NPEL	SVK	908	50			SKIN		
MV	SVN	308	50			SKIN		
WEL	GBR	308	50			SKIN		
OEL	EU	308	50			SKIN		
Predicted no-effect concentration	on - PNEC							
Normal value in fresh water				19	mg/	/I		
Normal value in marine water				1,9	mg/	/I		
Normal value for fresh water se	ediment			70,2	mg/	/kg		
Normal value for marine water :	sediment			7,02	mg/	/kg		
Normal value for the terrestrial compartment				274	mg/	/kg		
Health - Derived no-effect	t level - DNEL / Effects on consumers	DMEL			Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation				3.2 mg/m3				310 mg/m3
Skin				15 mg/kg bw/d				65 mg/kg bw/d



Revision nr. 2

Dated 06/06/2023

Printed on 06/06/2023

Page n. 8/25

Replaced revision:1 (Printed on: 09/09/2022)

B-LEM3 EXXTRA MG

LINALOOL Predicted no-effect concentration	on - PNEC							
Normal value in fresh water				200	μg,	/1		
Normal value in marine water				2	mg/l			
Normal value for fresh water se	ediment			2,22	mg	/kg dw		
Normal value for marine water sediment				222	μg	//kg dw		
Normal value of STP microorga	anisms			10	mg	/I		
Normal value for the food chair	n (secondary poison	ing)		7,8	mg	/kg		
Normal value for the terrestrial	compartment			327	μg	/kg dw		
Health - Derived no-effect		MEL						
	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		1,2 µg/kg		200 μg/kg		Зубіснію		Зузюние
Inhalation		bw/day 4,1 mg/m3	4,1	bw/day 700 μg/m³		16,5 mg/m3	16,5	2,8 mg/m3
Skin	1,5 mg/cm2	2,5 mg/kg bw/d	1,5 mg/cm2	1,25 mg/kg bw/d	3 mg/cm2	5 mg/kg bw/d	3 mg/cm2	2,5 mg/kg bw/d
BENZYL SALICYLATE								
Predicted no-effect concentration	on - PNEC							
Normal value in fresh water				0,00103	mg	/I		
Normal value in marine water			0,000103	mg	/I			
Normal value for fresh water sediment			0,583	mg	/kg dw			
Normal value for marine water sediment			0,0583	mg	/kg dw			
Normal value for water, intermi	ttent release			0,0103	mg	/I		
Normal value of STP microorga	anisms			10	mg	/I		
Normal value for the food chair	n (secondary poison	ing)		0,0527	mg	/kg food		
Normal value for the terrestrial	compartment			1,41	mg	/kg dw		
Health - Derived no-effect		MEL						
	Effects on consumers				Effects on workers			
Route of exposure Oral	Acute local	Acute systemic	Chronic local	Chronic systemic 0,790 mg/kg	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation				1,37 mg/m3				7,8 mg/m3
				0,790 mg/kg bw/d				2,21 mg/kg bw/d
Skin								
CITRONELLOL	on - PNEC							
CITRONELLOL Predicted no-effect concentration	on - PNEC			2,4	hд	<u></u>		
CITRONELLOL Predicted no-effect concentration Normal value in fresh water	on - PNEC			2,4	μg			
CITRONELLOL Predicted no-effect concentration Normal value in fresh water Normal value in marine water					ng			
CITRONELLOL Predicted no-effect concentration Normal value in fresh water Normal value in marine water Normal value for fresh water se	ediment			240	ng,	1		
CITRONELLOL Predicted no-effect concentration Normal value in fresh water Normal value in marine water Normal value for fresh water see Normal value for marine water Normal value for water, intermit	ediment sediment			240 25,6	ng,	'I 'kg dw 'kg dw		



Revision nr. 2

Dated 06/06/2023

Printed on 06/06/2023

Page n. 9/25

Replaced revision:1 (Printed on: 09/09/2022)

B-LEM3 EXXTRA MG

						ŀ	Replaced revision:1 (Print	ted on: 09/09/20
Health - Derived no-effe	ect level - DNEL / D	MEL						
	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				13,8 mg/kg bw/d				
Inhalation	10 mg/m3		10 mg/m3	47,8 mg/m3	10 mg/m3		10 mg/m3	161,6 mg/m
Skin	2,95 mg/cm2			196,4 mg/kg bw/d	2,95 mg/cm2			327,4 mg/kg bw/d
DIPENTENE Threshold Limit Value								
Type	Country	TWA/8h		STEL/15min		Rema		
		mg/m3	ppm	mg/m3	ppm	Obser	vations	
RD	LTU	150	25	300	50			
TLV	NOR	140	25	300	30			
				202 (2)	50 (0)			
NGV/KGV	SWE	150	25	300 (C)	50 (C)			
1,2-BENZISOTHIAZOL-								
Normal value in fresh water				4,03	μg/	1		
Normal value in marine wate	r			403	ng/			
Normal value for fresh water	sediment			49,9	μg/	1		
Normal value for marine water sediment				4,99	μg/	kg		
Normal value for water, inter	mittent release			1,1	μg/	1		
Normal value of STP microo	rganisms			1,03	mg.	/I		
Normal value for the terrestri	al compartment			3	mg.	/kg soil dw		
Health - Derived no-effe	ect level - DNEL / D	MEL						
	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic	Acute local	Acute	Chronic local	Chronic
Inhalation				systemic 1.2 mg/m3		systemic 6.81		systemic 6.81 mg/m3
Skin				345 µg/kg				966 µg/kg
				bw/d				bw/d
2-METHYL-2H-ISOTHIA Predicted no-effect concentra								
Normal value in fresh water				3,39	μg/	1		
Normal value in marine water	r			3,39	μg/	1		
Normal value for water, inter	mittent release			3,39	μg/	1		
Normal value of STP microo	rganisms			230	μg/	1		
Normal value for the terrestri	al compartment			47,1	μg	/kg soil dw		
Health - Derived no-effe	Effects on	MEL			Effects on			
	consumers		Chronic local	Chronic	workers Acute local	Acute	Chronic local	Chronic
Route of exposure	Acute local	Acute systemic	Cilionic local					
Route of exposure	Acute local 21 μg/m³	Acute systemic	43 µg/m³	systemic	43 μg/m³	systemic	21 μg/m³	systemic



Revision nr. 2

Dated 06/06/2023

Printed on 06/06/2023

Page n 10/25

Replaced revision:1 (Printed on: 09/09/2022)

B-LEM3 EXXTRA MG

Legend:

(C) = CEILING : INHAL = Inhalable Fraction : RESP = Respirable Fraction : THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available; NEA = no exposure expected; NPI = no hazard identified; LOW = low hazard; MED = medium hazard; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, failure time and permeability. The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.



Revision nr. 2

Dated 06/06/2023 Printed on 06/06/2023

Page n 11/25

Replaced revision:1 (Printed on: 09/09/2022)

B-LEM3 EXXTRA MG

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Information **Properties** Value Appearance liquid Method:visual Colour Violet

Odour lavender Method:own -5 °C Melting point / freezing point Method:own > 100 °C Initial boiling point Method:own

Flammability not flammable

Lower explosive limit not available Reason for missing data:it does not contain substances classified as explosive

Upper explosive limit not available Reason for missing data:it does not contain substances classified as explosive

Flash point > 60 °C Auto-ignition temperature > 200 °C

Substance: OXIRANE, 2-METHYL, POLYMER WITH OXIRANE, MONO (2-PROPILEPTYL) ETHER

>300 °C Substance: OXIRANE, 2-METHYL, POLYMER WITH OXIRANE, Decomposition temperature

MONO (2-PROPILEPTYL) ETHER рΗ $7,00 \pm 0,50$ Method:own

instrument: METTLER TOLEDO SEVEN GO

electrode: METTLER TOLEDO InLab 413 SG / 2m IP67

Kinematic viscosity 3,0 mm2/s Method:Calculation

not applicable

Dynamic viscosity 3,0 cP Method:BROOKFIELD DV1 LV (spindle=1 / speed=100 / T=20°C) Method:own

Solubility soluble in water in any ratio Partition coefficient: n-octanol/water Reason for missing data: The product is a blend not available

17,34 mmHg Vapour pressure Method:calculation Density and/or relative density 1,00 - 1,05 g/cm3 Method:Instrument: METTLER TOLEDO DENSITOPRO

not available Relative vapour density

9.2. Other information

Particle characteristics

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

VOC (Directive 2010/75/EU) 0,92 % - 9,24 g/litre VOC (volatile carbon) 0,60 % - 6,10 g/litre

Explosive properties not explosive Remark:it does not contain substances classified as explosive Oxidising properties not oxidizing Remark:it does not contain substances classified as oxidizing

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.



Revision nr. 2

Dated 06/06/2023

Printed on 06/06/2023

Page n. 12/25

Replaced revision:1 (Printed on: 09/09/2022)

B-LEM3 EXXTRA MG

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4. Conditions to avoid

Avoid contact with: oxidants, reducing agents, strong acids, strong bases

10.5. Incompatible materials

Avoid contact with: oxidants, reducing agents, strong acids, strong bases

10.6. Hazardous decomposition products

Carbon oxides: CO, CO2

SECTION 11. Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation) of the mixture:

Not classified (no significant component)

ATE (Oral) of the mixture: >2000 mg/kg

ATE (Dermal) of the mixture: Not classified (no significant component)

ALCOHOLS, C12-14, ETHOXYLATED, SULFATES, SODIUM SALTS (< 2.5 EO)

 $LD50 \ (Dermal): > 2000 \ mg/kg \ Ratto \ (OECD \ 402 \) \\ LD50 \ (Oral): > 2000 \ mg/kg \ Ratto \ (OECD \ 401 \)$

OXIRANE, 2-METHYL, POLYMER WITH OXIRANE, MONO (2-PROPILEPTYL) ETHER

LD50 (Oral): > 2000 mg/kg rat



Revision nr. 2

Dated 06/06/2023

Printed on 06/06/2023

Page n. 13/25

Replaced revision:1 (Printed on: 09/09/2022)

B-LEM3 EXXTRA MG

POLEY (OXY-1,2-ETHANYL), ALPHA -TRIDECYL- OMEGA -HYDROXY-, BRANCHED

LD50 (Dermal): > 2000 mg/kg rat (OECD - linea guida 402) LD50 (Oral): > 300 mg/kg rat (OECD-Linea guida 423)

DIPROPYLENE GLYCOL MONOMETHYL ETHER

 LD50 (Dermal):
 > 19020 mg/kg coniglio

 LD50 (Oral):
 > 5000 mg/kg ratto

 LC50 (Inhalation vapours):
 > 275 ppm/7h ratto

2-METHYL-2H-ISOTHIAZOL-3-ONE

LD50 (Dermal): 218 mg/kg Rabbit male. Method: calculation

LD50 (Oral): 183 mg/kg Rat, female

LC50 (Inhalation mists/powders): 0,11 mg/l/4h Rat male, female. Method: OECD Test Guideline 403

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY


Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class



Revision nr. 2

Dated 06/06/2023

Printed on 06/06/2023

Page n. 14/25

Replaced revision:1 (Printed on: 09/09/2022)

B-LEM3 EXXTRA MG

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

OXIRANE, 2-METHYL, POLYMER WITH OXIRANE, MONO (2-PROPILEPTYL)

ETHER

LC50 - for Fish > 10 mg/l/96h Pesci (OECD 203; ISO 7346; 92/69/CEE, C.1)

EC50 - for Crustacea > 10 mg/l/48h dafnie (OECD - linea guida 202, parte 1)

> 10 mg/l/72h alghe (OECD - linea guida 201)

EC10 for Algae / Aquatic Plants > 1 mg/l/72h (OECD - linea guida 201)

Chronic NOEC for Fish > 1 mg/l Pesci (Linea Guida OECD 215)

Chronic NOEC for Crustacea > 1 mg/l Daphnia magna (OECD - linea guida 211)

2-METHYL-2H-ISOTHIAZOL-3-ONE

EC50 - for Algae / Aquatic Plants

LC50 - for Fish > 150 mg/l/96h Danio rerio EC50 - for Crustacea 0.87 μ g/l/48h Daphnia magna

EC50 - for Algae / Aquatic Plants 0,157 mg/l/72h Pseudokirchneriella subcapitata
Chronic NOEC for Algae / Aquatic Plants 0,0104 mg/l Pseudokirchneriella subcapitata

DIPROPYLENE GLYCOL MONOMETHYL

ETHER

LC50 - for Fish > 1000 mg/l/96h poecilia reticulata EC50 - for Crustacea 1919 mg/l/48h daphnia magna

EC50 - for Algae / Aquatic Plants > 969 mg/l/72h Selenastrum capricornutum

ALCOHOLS, C12-14, ETHOXYLATED, SUI FATES, SODIUM SALTS (< 2.5 FO)

SULFATES, SODIUM SALTS (< 2.5 EO) LC50 - for Fish

 ${\sf EC50 - for\ Crustacea} \\ {\sf > 1\ mg/l/48h\ Daphnia\ magna\ (Pulce\ d'acqua\ grande)\ (\ OECD\ TG\ 202\)} \\$

EC50 - for Algae / Aquatic Plants > 10 mg/l/72h Desmodesmus subspicatus (alga verde) (OECD TG 201)

Chronic NOEC for Fish 14 mg/l Oncorhynchus mykiss (Trota iridea) - NOEC (28 D) (OECD TG 204

> 1 mg/l/96h Brachydanio rerio (danio zebrato o pesce zebra) (OECD 203)

Chronic NOEC for Crustacea 27 mg/l Daphnia magna (Pulce d'acqua grande) (OECD TG 211)

Chronic NOEC for Algae / Aquatic Plants 0,93 mg/l Desmodesmus subspicatus (alga verde) - NOEH (72 h) (OECD

TG 201)



Revision nr. 2

Dated 06/06/2023 Printed on 06/06/2023

Page n. 15/25

Replaced revision:1 (Printed on: 09/09/2022)

B-LEM3 EXXTRA MG

> 1 mg/l/96h leuciscus idus

POLEY (OXY-1,2-ETHANYL), ALPHA -TRIDECYL- OMEGA -HYDRÓXY-,

BRANCHED LC50 - for Fish

> 1 mg/l/48hEC50 - for Crustacea EC50 - for Algae / Aquatic Plants > 1 mg/l/72h

Chronic NOEC for Crustacea > 1 mg/l Daphnia magna (OECD - linea guida 202, parte 2, semistatico)

12.2. Persistence and degradability

OXIRANE, 2-METHYL, POLYMER WITH OXIRANE, MONO (2-PROPILEPTYL) **ETHER**

Rapidly degradable

2-METHYL-2H-ISOTHIAZOL-3-ONE

489 g/l Solubility in water

NOT rapidly degradable

DIPROPYLENE GLYCOL MONOMETHYL

FTHFR

Solubility in water 1000 mg/l

Rapidly degradable

ALCOHOLS, C12-14, ETHOXYLATED, SULFATES, SODIUM SALTS (< 2.5 EO)

Rapidly degradable

POLEY (OXY-1,2-ETHANYL), ALPHA -TRIDECYL- OMEGA -HYDROXY-, **BRANCHED**

Rapidly degradable

12.3. Bioaccumulative potential

2-METHYL-2H-ISOTHIAZOL-3-ONE

Partition coefficient: n-octanol/water -0,32 Log Kow

DIPROPYLENE GLYCOL MONOMETHYL

ETHER

Partition coefficient: n-octanol/water 0,004

POLEY (OXY-1,2-ETHANYL), ALPHA -TRIDECYL- OMEGA -HYDROXY-,

BRANCHED

Partition coefficient: n-octanol/water 4,73 25°C

12.4. Mobility in soil

ALCOHOLS, C12-14, ETHOXYLATED, SULFATES, SODIUM SALTS (< 2.5 EO)

Partition coefficient: soil/water 2,2 calcolato



Revision nr. 2

Dated 06/06/2023

Page n. 16/25

Replaced revision:1 (Printed on: 09/09/2022)

B-LEM3 EXXTRA MG

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

14.1. UN number or ID number

not applicable

14.2. UN proper shipping name

not applicable

14.3. Transport hazard class(es)

not applicable

14.4. Packing group

not applicable

14.5. Environmental hazards

not applicable

14.6. Special precautions for user

not applicable



Revision nr. 2

Dated 06/06/2023

Page n. 17/25

Replaced revision:1 (Printed on: 09/09/2022)

B-LEM3 EXXTRA MG

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 3 - 40

Contained substance

Point 75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage ≥ than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.



Revision nr. 2

Dated 06/06/2023

Printed on 06/06/2023

Page n. 18/25

Replaced revision:1 (Printed on: 09/09/2022)

B-LEM3 EXXTRA MG

Regulation (EC) No. 648/2004

Ingredients according to Regulation (EC) No. 648/2004

The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No. 648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Acute Tox. 2 Acute toxicity, category 2

Acute Tox. 3 Acute toxicity, category 3

Acute Tox. 4 Acute toxicity, category 4

Skin Corr. 1B Skin corrosion, category 1B

Eye Dam. 1 Serious eye damage, category 1

Eye Irrit. 2 Eye irritation, category 2
Skin Irrit. 2 Skin irritation, category 2
Skin Sens. 1A Skin sensitization, category 1A

Aquatic Acute 1 Hazardous to the aquatic environment, acute toxicity, category 1

Aquatic Chronic 1 Hazardous to the aquatic environment, chronic toxicity, category 1

Aquatic Chronic 3 Hazardous to the aquatic environment, chronic toxicity, category 3

H330 Fatal if inhaled.H301 Toxic if swallowed.H311 Toxic in contact with skin.

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.H319 Causes serious eye irritation.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.H412 Harmful to aquatic life with long lasting effects.

EUH071 Corrosive to the respiratory tract.

EUH210 Safety data sheet available on request.



Revision nr. 2

Dated 06/06/2023 Printed on 06/06/2023

Page n 19/25

Replaced revision:1 (Printed on: 09/09/2022)

B-LEM3 EXXTRA MG

Use descriptor system:

ERC Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) **ERC** 8d Widespread use of non- reactive processing aid (no inclusion into or onto article, outdoor)

LCS C Consumer use

РW LCS Widespread use by professional workers

Washing and cleaning products PC 35 PROC 10 Roller application or brushing

PROC 8a Transfer of substance or mixture (charging and discharging) at non- dedicated facilities

_EGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
- 4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
- Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP) 14. Regulation (EU) 2018/669 (XI Atp. CLP)
- 15. Regulation (EU) 2019/521 (XII Atp. CLP)
- 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)



Revision nr. 2

Dated 06/06/2023

Printed on 06/06/2023

Page n. 20/25

Replaced revision:1 (Printed on: 09/09/2022)

B-LEM3 EXXTRA MG

17. Regulation (EU) 2019/1148

18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)

19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)

20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)

21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)

22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
- The Merck Index. - 10th Edition
- Handling Chemical Safety

INRS - Fiche Toxicologique (toxicological sheet)

Patty - Industrial Hygiene and Toxicology

- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review: The following sections were modified: 01 / 02 / 03 / 09 / 10 / 11 / 12 / 15 / 16.



Revision nr. 2

Dated 06/06/2023

Printed on 06/06/2023

Page n. 21/25

Replaced revision:1 (Printed on: 09/09/2022)

B-LEM3 EXXTRA MG

SUMI Safe Use of Mixtures Information





AISE_SUMI_PW_8a_1_G

Version 1.1, August 2018

Transfer of product to a container (bottle/bucket/machine)

This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.

General description of the process covered

This SUMI applies to professional uses where the product is transferred to or diluted in a container, such as a dispenser, bottle or bucket. This Safe Use Information is based on the AISE_SWED_PW_8a_1_L e AISE_SWED_PW_8a_1_S.

Operational Conditions

Maximum duration	60 minutes per day.
Range of application /	Indoor Use.
Process conditions	Process carried out at room temperature.
	In case of dilution, tap water at a maximum temperature of 45°C is used.
Air exchange rate	Provide a basic standard of general ventilation (1 to 3 air changes per hour). No LEV required.

Risk Management Measures

Measures related to personal protective equipment (PPE), hygiene and health evaluation	Wear suitable gloves and eye protection. See section 8 of the SDS of this product for specifications				
	Training of workers in relation to proper use and maintenance of PPEs must be ensured.				
Environmental	Prevent that undiluted product reaches surface waters.				
measures	If appropriate I'AISE SPERC 8a.1.a.v2 : wide dispersive use resulting in release to municipal sewage treatment plant.				



Revision nr. 2

Dated 06/06/2023

Printed on 06/06/2023

Page n. 22/25

Replaced revision:1 (Printed on: 09/09/2022)

B-LEM3 EXXTRA MG

Additional good practice advice

Don't eat or drink. Don't smoke. Don't use in proximity of open flame.	
Wash hands after use. Avoid contact with damaged skin. Do not mix with other products.	2! 2
Spillage instructions	Dilute with fresh water and mop up.
Hygiene practices	Follow the product instructions as specified on the label or in the product information sheet and

Additional information depending on product composition

The label and (when required) the Safety Data Sheet contain additional, product specific information crucial for working safely with mixtures. Please refer to the product label and SDS for information including, but not limited to: product hazard classification, potentially allergenic fragrances, notable ingredients and threshold limit values (when available).

use good occupational hygiene practices as specified in Section 7 of the product SDS.

Disclaimer

This is a document for communicating generic conditions of safe use of a product. It is the responsibility of the formulator to link this SUMI to the SDS of a specific product that he is selling. If a SUMI (or associated SWED) code is mentioned in the SDS of a product, the formulator of that product declares that all substances in the mixture are present in such concentration, that the use of the product within the conditions of the SUMI is safe. When available, this safe use is ensured by evaluating the results of the chemical safety assessments as performed by the raw material suppliers. When no chemical safety assessment has been carried out by the supplier for an ingredient that contributes to the classification of the mixture, the formulator has performed a safety assessment himself. Following Occupational Health legislation, the employer of workers that use products that are assessed as safe following SUMI conditions remains responsible for communicating relevant use information to employees. When developing workplace instructions for employees, SUMI Sheets should always be considered in combination with the SDS and the label of the product. This document is provided by A.I.S.E. for general information purposes only. The formulator uses the content of this document at its sole risk. A.I.S.E. disclaims any liability to any person or entity for any loss, damage no matter of what kind (actual, consequential, punitive or otherwise), injury, claim, liability or other cause of any kind or character based upon or resulting from the use (even partly) of the content of this document.



B-LEM3 EXXTRA MG

Revision nr. 2

Dated 06/06/2023

Printed on 06/06/2023

Page n. 23/25

Replaced revision:1 (Printed on: 09/09/2022)

SUMI Safe Use of Mixtures Information





AISE_SUMI_PW_10_2_G

Version 1.1, August 2018

Professional uses; Brushing after trigger spraying or brushing with tools

This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.

General description of the process covered

This SUMI applies to professional uses where the product is brushed on a surface, with limited exposure to the hands, either after trigger spraying or through the use of tools such as a mop. This Safe Use Information is based on the AISE_SWED_PW_10_2.

Operational Conditions

Maximum duration	480 minutes per day.	
Range of application / Process conditions		
Process conditions	Process carried out at room temperature.	
	In case of dilution, tap water at a maximum temperature of 45°C is used.	
Air exchange rate	Provide a basic standard of general ventilation (1 to 3 air changes per hour). No LEV required.	

Risk Management Measures

Measures related to personal protective equipment (PPE), hygiene and health evaluation	Wear suitable gloves and eye protection. See section 8 of the SDS of this product for specifications.
	Training of workers in relation to proper use and maintenance of PPEs must be ensured.
Environmental	Prevent that undiluted product reaches surface waters.
measures	If appropriate l'AISE SPERC 8a.1.a.v2 may apply : wide dispersive use resulting in release to municipal sewage treatment plant.



Revision nr. 2

Dated 06/06/2023

Printed on 06/06/2023

Page n. 24/25

Replaced revision:1 (Printed on: 09/09/2022)

B-LEM3 EXXTRA MG

Additional good practice advice

Don't eat or drink. Don't smoke. Don't use in proximity of open flame.	
Wash hands after use. Avoid contact with damaged skin. Do not mix with other products.	
Spillage instructions	Dilute with fresh water and mop up.
Hygiene practices	Follow the product instructions as specified on the label or in the product information sheet and use good occupational hygiene practices as specified in Section 7 of the product SDS.

Additional information depending on product composition

The label and (when required) the Safety Data Sheet contain additional, product specific information crucial for working safely with mixtures. Please refer to the product label and SDS for information including, but not limited to: product hazard classification, potentially allergenic fragrances, notable ingredients and threshold limit values (when available).

Disclaimer

This is a document for communicating generic conditions of safe use of a product. It is the responsibility of the formulator to link this SUMI to the SDS of a specific product that he is selling. If a SUMI (or associated SWED) code is mentioned in the SDS of a product, the formulator of that product declares that all substances in the mixture are present in such concentration, that the use of the product within the conditions of the SUMI is safe. When available, this safe use is ensured by evaluating the results of the chemical safety assessments as performed by the raw material suppliers. When no chemical safety assessment has been carried out by the supplier for an ingredient that contributes to the classification of the mixture, the formulator has performed a safety assessment himself. Following Occupational Health legislation, the employer of workers that use products that are assessed as safe following SUMI conditions remains responsible for communicating relevant use information to employees. When developing workplace instructions for employees, SUMI Sheets should always be considered in combination with the SDS and the label of the product. This document is provided by A.I.S.E. for general information purposes only. The formulator uses the content of this document at its sole risk. A.I.S.E. disclaims any liability to any person or entity for any loss, damage no matter of what kind (actual, consequential, punitive or otherwise), injury, claim, liability or other cause of any kind or character based upon or resulting from the use (even partly) of the content of this document



Dated 06/06/2023

Revision nr. 2

Printed on 06/06/2023

Page n. 25/25

Replaced revision:1 (Printed on: 09/09/2022)

B-LEM3 EXXTRA MG

WORKING INSTRUCTIONS SHEET

The purpose of this sheet is to provide the personnel carrying out the cleaning operations with instructions for an appropriate and safe use of the products and for the correct management of emergency situations.

Operation planned	Transfer of substance or mixture (charging and discharging) at non- dedicated facilities [PROC8a]. Roller application or brushing [PROC10];
Product name	B-LEM3 EXXTRA MG
Risks of the product as it is	H319 Causes serious eye irritation. H317 May cause an allergic skin reaction.
Risks of the product at the maximum concentration of use (3 %)	At the maximum recommended use concentration the product is classified Not dangerous according to Regulation (EC) No. 1272/2008
Handling of the product as it is	Handle the product after consulting all the other sections of this safety data sheet. Avoid the dispersion of the product in the environment. Do not eat, drink or smoke during use. Remove contaminated clothing and protective equipment before entering eating areas
Handling of the product at the maximum concentration of use (3 %)	At work do not eat or drink
PPE required For product as it is (transfer, concentrated use)	Protect hands with category III work gloves (see standard EN 374). Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wear airtight protective goggles (see standard EN 166).
PPE required for the product at the maximum concentration of use (3 %)	Protect hands with category III work gloves (see standard EN 374).
In case of emergency (accidents involving exposure to the product)	Inform the client immediately. Immediately notify the employer. Contact the Anti-Poison Center listed in section 1.4 of the SDS
In case of accidental spillage of large quantities In concentrated form	Wear gloves, goggles and protective clothing (for specifications refer to to section 8.2. of the SDS). Suck up the leaked product into a suitable container. Evaluate the compatibility of the container to be used with the product, checking the sect. 10 of the SDS. Absorb the remainder with inert absorbent material. Provide sufficient ventilation of the place affected by the leak. The disposal of contaminated material must be carried out in accordance with the provisions of section 13 of the SDS
In case of accidental spillage of large quantities at the maximum use concentration (3 %)	Wear gloves, goggles and protective clothing (for specifics refer to section 8.2. Of the SDS of the product as it is). Suck up the leaked product into a suitable container. Evaluate the compatibility of the container to be used with the product, checking the sect. 10 of the SDS of the product as it is Absorb the remainder with inert absorbent material. Provide sufficient ventilation of the place affected by the leak. The disposal of contaminated material must be carried out in accordance with the provisions of section 13 of the SDS of the product as it is.
Product storage	Keep only in the original container. Keep the containers closed, in a well-ventilated place, away from direct sunlight. Keep the containers away from any incompatible materials, checking the sect 10 of the SDS
In case of accidents, emergencies or fire in the work area	Immediately notify the client, the employer. Follow the instructions for emergencies. Follow the instructions in sect. 5 of the SDS