

**BELLINZONI S.R.L.**

Revision nr. 1

Dated 12/12/2022

B-GTX PULITORE FUGHE

Printed on 12/12/2022

Page n. 1/23

Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: P104DGTX - P104DGTX07L
Product name: B-GTX PULITORE FUGHE
UFI: W3J0-P0H4-P00M-9R9H

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: Alkaline detergent for cleaning cement joints

| Identified Uses | Industrial | Professional | Consumer |
|---|------------|--|------------------------------------|
| Alkaline detergent for cleaning cement joints | - | ERC: 8a, 8d. PROC: 11. PC: 35. LCS: PW. | ERC: 8a, 8d. PC: 35. LCS: C. |

1.3. Details of the supplier of the safety data sheet

Name: BELLINZONI S.R.L.
Full address: Via Mezzano 64
District and Country: 28069 Trecate (NO)
Italia
Tel. +39 0321 770558

e-mail address of the competent person

responsible for the Safety Data Sheet: laboratorio@bellinzoni.com
Supplier: BELLINZONI S.r.l.

1.4. Emergency telephone number

For urgent inquiries refer to

- CAV "Osp. Pediatrico Bambino Gesù" Dip. Emergenza e Accettazione DEA – Roma - Piazza Sant' Onofrio, 4 CAP: 00165 – Telefono: 06 68593726 – Responsabile: Marco Marano
- Az. Osp. Univ. Foggia – Foggia - V.le Luigi Pinto, 1 – CAP: 71122 – Telefono: 800183459 – Responsabile: Anna Lepore
- Az. Osp. "A. Cardarelli" – Napoli - Via A. Cardarelli, 9 – CAP: 80131081- Telefono: 5453333 – Responsabile: Romolo Villani
- CAV Policlinico "Umberto I" - Roma - V.le del Policlinico, 155 – CAP: 161 – Telefono: 06-49978000 – Responsabile: M. Caterina Grassi
- CAV Policlinico "A. Gemelli" - Roma - Largo Agostino Gemelli, 8 – CAP: 168 – Telefono: 06-3054343 – Responsabile: Alessandro Barelli
- Az. Osp. "Careggi" U.O. Tossicologia Medica – Firenze - Largo Brambilla, 3 – CAP: 50134 – Telefono: 055-7947819 – Responsabile: Francesco Gambassi
- CAV Centro Nazionale di Informazione Tossicologica - Pavia – Via Salvatore Maugeri, 10 – CAP: 27100 - Telefono: 0382-24444 – Responsabile: Carlo Locatelli
- Osp. Niguarda Ca' Granda – Milano - Piazza Ospedale Maggiore,3 – CAP: 20162 – Telefono: 02-66101029 – Responsabile: Franca Davanzo
- Azienda Ospedaliera Papa Giovanni XXII – Bergamo - Piazza OMS, 1 – CAP: 24127 – Telefono: 800883300 – Responsabile: Bacis Giuseppe
- Azienda Ospedaliera Integrata Verona – Verona - Piazzale Aristide Stefani, 1 – CAP: 37126 – Telefono 800011858 – Responsabile: Giorgio Ricci

B-GTX PULITORE FUGHE**SECTION 2. Hazards identification****2.1. Classification of the substance or mixture**

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

| | | |
|--|------|--|
| Substance or mixture corrosive to metals, category 1 | H290 | May be corrosive to metals. |
| Skin corrosion, category 1A | H314 | Causes severe skin burns and eye damage. |
| Serious eye damage, category 1 | H318 | Causes serious eye damage. |

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: Danger

Hazard statements:

| | |
|---------------|--|
| H290 | May be corrosive to metals. |
| H314 | Causes severe skin burns and eye damage. |
| EUH210 | Safety data sheet available on request. |

Precautionary statements:

| | |
|-----------------------|--|
| P102 | Keep out of reach of children. |
| P260 | Do not breathe dust / fume / gas / mist / vapours / spray. |
| P280 | Wear protective gloves/ protective clothing / eye protection / face protection. |
| P301+P330+P331 | IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. |
| P303+P361+P353 | IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |

Contains: POTASSIUM HYDROXIDE, SODIUM METASILICATE PENTAHYDRATE

Ingredients according to Regulation (EC) No. 648/2004

Less than 5% anionic surfactants, non-ionic surfactants, soap, polycarboxylates

Dye. Benzyl alcohol

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration \geq 0.1%.

B-GTX PULITORE FUGHE**SECTION 3. Composition/information on ingredients****3.1. Substances**

Information not relevant

3.2. Mixtures

Contains:

| Identification | x = Conc. % | Classification (EC) 1272/2008 (CLP) |
|---|-------------|--|
| 2-BUTOXYETHANOL | | |
| INDEX 603-014-00-0 | 5 ≤ x < 6 | Acute Tox. 4 H302, Acute Tox. 4 H332, Eye Irrit. 2 H319, Skin Irrit. 2 H315 |
| EC 203-905-0 | | LD50 Oral: 1200 mg/kg bw/day, STA Inhalation vapours: 11 mg/l |
| CAS 111-76-2 | | |
| REACH Reg. 01-2119475108-36 | | |
| POTASSIUM HYDROXIDE | | |
| INDEX 019-002-00-8 | 3 ≤ x < 4 | Met. Corr. 1 H290, Acute Tox. 4 H302, Skin Corr. 1A H314, Eye Dam. 1 H318 |
| EC 215-181-3 | | Skin Corr. 1B H314: ≥ 2%, Skin Irrit. 2 H315: ≥ 0,5%, Eye Dam. 1 H318: ≥ 2%, Eye Irrit. 2 H319: ≥ 0,5% |
| CAS 1310-58-3 | | LD50 Oral: 333 mg/kg |
| REACH Reg. 01-2119487136-33 | | |
| BENZYL ALCOHOL | | |
| INDEX 603-057-00-5 | 2 ≤ x < 3 | Acute Tox. 4 H302, Acute Tox. 4 H332, Eye Irrit. 2 H319 |
| EC 202-859-9 | | LD50 Oral: 1620 mg/kg, STA Inhalation vapours: 11 mg/l |
| CAS 100-51-6 | | |
| REACH Reg. 01-2119492630-38 | | |
| SODIUM METASILICATE PENTAHYDRATE | | |
| INDEX - | 1 ≤ x < 2 | Met. Corr. 1 H290, Skin Corr. 1B H314, Eye Dam. 1 H318, STOT SE 3 H335 |
| EC 229-912-9 | | |
| CAS 10213-79-3 | | |
| REACH Reg. 01-2119449811-37-XXXX | | |
| SODIUM P-CUMENESULPHONATE | | |
| INDEX | 1 ≤ x < 2 | Eye Irrit. 2 H319 |
| EC - | | |
| CAS 15763-76-5 | | |
| REACH Reg. 01-2119489411-37-0004 | | |

The full wording of hazard (H) phrases is given in section 16 of the sheet.

**B-GTX PULITORE FUGHE****SECTION 4. First aid measures****4.1. Description of first aid measures**

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures**5.1. Extinguishing media****SUITABLE EXTINGUISHING EQUIPMENT**

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture**HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE**

Do not breathe combustion products.

5.3. Advice for firefighters**GENERAL INFORMATION**

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

**B-GTX PULITORE FUGHE****6.3. Methods and material for containment and cleaning up**

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage**7.1. Precautions for safe handling**

Ensure that there is an adequate earthing system for the equipment and personnel. Avoid contact with eyes and skin. Do not breathe powders, vapours or mists. Do not eat, drink or smoke during use. Wash hands after use. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a ventilated and dry place, far away from sources of ignition. Keep containers well sealed. Keep the product in clearly labelled containers. Avoid overheating. Avoid violent blows. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection**8.1. Control parameters**

Regulatory References:

| | | |
|-----|------------------|--|
| AUS | Österreich | Gesamte Rechtsvorschrift für Grenzwerteverordnung 2021 , Fassung vom 17.06.2021 |
| BEL | Belgique | Liste de valeurs limites d'exposition aux agents chimiques, livre VI du code du bien-être au travail |
| BGR | България | НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г. ЗА ЗАЩИТА НА РАБОТЕЩИТЕ ОТ РИСКОВЕ, СВЪРЗАНИ С ЕКСПОЗИЦИЯ НА ХИМИЧНИ АГЕНТИ ПРИ РАБОТА (изм. ДВ. бр.5 от 17 Януари 2020г.) |
| CHE | Suisse / Schweiz | Valeurs limites d'exposition aux postes de travail: VME/VLE (SUVA). Grenzwerte am Arbeitsplatz: MAK (SUVA) |
| CYP | Κύπρος | Οι περί Αζθάλειαρ και Υγείαρ ζηην Δπραζία (Φημικοί Παπάγονηρ) (Τποποποιητικοί) Κανονιζμοί ηος 2019. Οι περί Ασφάλειας και Υγείας στην Εργασία (Καρκινογόνοι και Μεταλλαξιογόνοι Παράγοντες) (Τροποποιητικοί) Κανονισμοί του 2020 |
| CZE | Česká Republika | Nařízení vlády č. 41/2020 Sb. Nařízení vlády, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci, ve znění pozdějších předpisů |
| DEU | Deutschland | Technischen Regeln für Gefahrstoffe (TRGS 900) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte. MAK- und BAT-Werte-Liste 2020, Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe, Mitteilung 56 |
| DNK | Danmark | Bekendtgørelse om grænseværdier for stoffer og materialer - BEK nr 1458 af 13/12/2019 |
| ESP | España | Límites de exposición profesional para agentes químicos en España 2021 |
| EST | Eesti | Ohtlike kemikaalide ja neid sisaldavate materjalide kasutamise töötervishoiu ja tööohutuse nõuded ning töökeskkonna keemiliste ohutegurite piirnormid [RT I, 17.10.2019, 1 - jõust. 17.01.2020] |
| FRA | France | Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS |
| FIN | Suomi | HTP-VÄRDEN 2020. Koncentrationer som befunnits skadliga. SOCIAL - OCH HÄLSOVÄRDSMINISTERIETS PUBLIKATIONER 2020:25 |
| GRC | Ελλάδα | Π.Δ. 26/2020 (ΦΕΚ 50/Α' 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ ``σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξιογόνους παράγοντες κατά την εργασία``» |
| HUN | Magyarország | Az innovációért és technológiáért felelős miniszter 5/2020. (II. 6.) ITM rendelete a kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről |
| HRV | Hrvatska | Pravilnik o izmjenama i dopunama Pravilnika o zaštiti radnika od izloženosti opasnim kemikalijama na radu, |

B-GTX PULITORE FUGHE

| | | |
|-----|----------------|---|
| ITA | Italia | graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 1/2021) |
| IRL | Éire | Decreto Legislativo 9 Aprile 2008, n.81 |
| LUX | Luxembourg | 2020 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations (2001-2015) and the Safety, Health and Welfare at Work (Carcinogens) Regulations (2001-2019) |
| LTU | Lietuva | Règlement grand-ducal du 24 janvier 2020 modifiant le règlement grand-ducal du 14 novembre 2016 concernant la protection des salariés contre les risques liés à l'exposition à des agents cancérigènes ou mutagènes au travail |
| LVA | Latvija | Jsakymas dėl lietuvių higienos normos hn 23:2011 „cheminių medžiagų profesinio poveikio ribiniai dydžiai. Matavimo ir poveikio vertinimo bendrieji reikalavimai“ patvirtinimo |
| MLT | Malta | Grozījumi Ministru kabineta 2007. gada 15. maija noteikumos Nr. 325 "Darba aizsardzības prasības saskarē ar ķīmiskajām vielām darba vietās" (prot. Nr. 32 18. §; prot. Nr. 1 22. §) |
| NOR | Norge | PROTECTION OF THE HEALTH AND SAFETY OF WORKERS FROM THE RISKS RELATED TO CHEMICAL AGENTS AT WORK REGULATIONS (S.L.424.24). PROTECTION OF WORKERS FROM THE RISKS RELATED TO EXPOSURE TO CARCINOGENS OR MUTAGENS AT WORK REGULATIONS (S.L.424.22) |
| NLD | Nederland | Forskrift om endring i forskrift om tiltaksverdi og grenseverdi for fysiske og kjemiske faktorer i arbeidsmiljøet samt smittesikogrupper for biologiske faktorer (forskrift om tiltaks- og grenseverdi), 21. august 2018 nr. 1255 |
| PRT | Portugal | Arbeidsomstandighedenregeling. Lijst van wettelijke grenswaarden op grond van de artikelen 4.3, eerste lid, en 4.16, eerste lid, van het Arbeidsomstandighedenbesluit |
| POL | Polska | Decreto-Lei n.º 1/2021 de 6 de janeiro, valores-limite de exposição profissional indicativos para os agentes químicos. Decreto-Lei n.º 35/2020 de 13 de julho, proteção dos trabalhadores contra os riscos ligados à exposição durante o trabalho a agentes cancerígenos ou mutagénicos |
| ROU | România | Rozporządzenie ministra rozwoju, pracy i technologii z dnia 18 lutego 2021 r. Zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w środowisku pracy |
| SWE | Sverige | Hotărârea nr. 53/2021 pentru modificarea hotărârii guvernului nr. 1.218/2006, precum și pentru modificarea și completarea hotărârii guvernului nr. 1.093/2006 |
| SVK | Slovensko | Hygieniska gränsvärden, Arbetsmiljöverkets föreskrifter och allmänna råd om hygieniska gränsvärden (AFS 2018:1) |
| SVN | Slovenija | NARIADENIE VLÁDY Slovenskej republiky z 12. augusta 2020, ktorým sa mení a dopĺňa nariadenie vlády Slovenskej republiky č. 356/2006 Z. z. o ochrane zdravia zamestnancov pred rizikami súvisiacimi s expozíciou karcinogénym a mutagénym faktorom pri práci v znení neskorších predpisov |
| TUR | Türkiye | Pravilnik o varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu (Uradni list RS, št. 100/01, 39/05, 53/07, 102/10, 43/11 – ZVZD-1, 38/15, 78/18 in 78/19) |
| GBR | United Kingdom | Kimyasal Maddelerle Çalışmalarda Sağlık ve Güvenlik Önlemleri Hakkında Yönetmelik 12.08.2013 / 28733 |
| EU | OEL EU | EH40/2005 Workplace exposure limits (Fourth Edition 2020) |
| | TLV-ACGIH | Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC. ACGIH 2021 |

2-BUTOXYETHANOL
Threshold Limit Value

| Type | Country | TWA/8h | | STEL/15min | | Remarks / Observations |
|---------|---------|--------|------|------------|--------|--|
| | | mg/m3 | ppm | mg/m3 | ppm | |
| MAK | AUS | 98 | 20 | 200 | 40 | SKIN STEL:30', Häufigkeit/Sch:4x |
| VLEP | BEL | 98 | 20 | 246 | 50 | SKIN |
| TLV | BGR | 98 | 20 | 246 | 50 | SKIN |
| MAK | CHE | 49 | 10 | 98 | 20 | SKIN |
| VME/VLE | CHE | 49 | 10 | 98 | 20 | SKIN |
| TLV | CYP | 98 | 20 | 246 | 50 | SKIN |
| TLV | CZE | 100 | 20,7 | 200 | 41,4 | SKIN |
| AGW | DEU | 49 | 10 | 98 (C) | 20 (C) | SKIN |
| MAK | DEU | 49 | 10 | 98 | 20 | SKIN Hinweis |
| TLV | DNK | 98 | 20 | | | SKIN E |
| VLA | ESP | 98 | 20 | 245 | 50 | SKIN |
| TLV | EST | 98 | 20 | 246 | 50 | SKIN |
| VLEP | FRA | 49 | 10 | 246 | 50 | SKIN |

B-GTX PULITORE FUGHE

| | | | | | | |
|-----------|-----|-----|----|-----|----|------|
| HTP | FIN | 98 | 20 | 250 | 50 | SKIN |
| TLV | GRC | 120 | 25 | | | |
| AK | HUN | 98 | | 246 | | SKIN |
| GVI/KGVI | HRV | 98 | 20 | 246 | 50 | SKIN |
| VLEP | ITA | 98 | 20 | 246 | 50 | SKIN |
| OELV | IRL | 98 | 20 | 246 | 50 | SKIN |
| VL | LUX | 98 | 20 | 246 | 50 | SKIN |
| RD | LTU | 50 | 10 | 100 | 20 | SKIN |
| RV | LVA | 98 | 20 | 246 | 50 | SKIN |
| TLV | MLT | 98 | 20 | 246 | 50 | SKIN |
| TLV | NOR | 50 | 10 | | | SKIN |
| TGG | NLD | 100 | | 246 | | SKIN |
| VLE | PRT | 98 | 20 | 246 | 50 | SKIN |
| NDS/NDSCh | POL | 98 | | 200 | | SKIN |
| TLV | ROU | 98 | 20 | 246 | 50 | SKIN |
| NGV/KGV | SWE | 50 | 10 | 246 | 50 | SKIN |
| NPEL | SVK | 98 | 20 | 246 | 50 | SKIN |
| MV | SVN | 98 | 20 | 246 | 50 | SKIN |
| ESD | TUR | 98 | 20 | 246 | 50 | SKIN |
| WEL | GBR | 123 | 25 | 246 | 50 | SKIN |
| OEL | EU | 98 | 20 | 246 | 50 | SKIN |
| TLV-ACGIH | | 97 | 20 | | | |

Predicted no-effect concentration - PNEC

| | | |
|---|-----|-------|
| Normal value in fresh water | 88 | mg/l |
| Normal value in marine water | 88 | mg/l |
| Normal value for fresh water sediment | 346 | mg/kg |
| Normal value for marine water sediment | 346 | mg/kg |
| Normal value for water, intermittent release | 91 | mg/l |
| Normal value of STP microorganisms | 463 | mg/l |
| Normal value for the food chain (secondary poisoning) | 2 | g/kg |
| Normal value for the terrestrial compartment | 233 | mg/kg |

Health - Derived no-effect level - DNEL / DMEL

| Route of exposure | Effects on consumers | | | Effects on workers | | | | |
|-------------------|----------------------|----------------|---------------|--------------------|-------------|----------------|---------------|------------------|
| | Acute local | Acute systemic | Chronic local | Chronic systemic | Acute local | Acute systemic | Chronic local | Chronic systemic |
| Oral | 26.7 mg/kg bw/d | | | 6.3 mg/kg bw/d | | | | |
| Inhalation | 147 mg/m3 | 426 mg/m3 | | 59 mg/m3 | 246 mg/m3 | 1091 mg/m3 | | 98 mg/m3 |
| Skin | 89 mg/kg bw/d | | | 75 mg/kg bw/d | | 89 mg/kg bw/d | | 125 mg/kg bw/d |

B-GTX PULITORE FUGHE
POTASSIUM HYDROXIDE
Threshold Limit Value

| Type | Country | TWA/8h | | STEL/15min | | Remarks / Observations |
|-----------|---------|--------|-----|------------|-----|------------------------|
| | | mg/m3 | ppm | mg/m3 | ppm | |
| MAK | AUS | 2 | | | | INHAL |
| VLEP | BEL | | | 2 (C) | | |
| TLV | BGR | 2 | | | | |
| MAK | CHE | 2 | | | | |
| VME/VLE | CHE | 2 | | | | |
| TLV | CZE | 1 | | 2 | | |
| TLV | DNK | | | 2 (C) | | |
| VLA | ESP | 1 | | 4 | | RESP |
| TLV | EST | 2 | | | | |
| VLEP | FRA | | | 2 | | |
| HTP | FIN | | | 2 (C) | | |
| TLV | GRC | 2 | | 2 | | |
| AK | HUN | 2 | | 2 | | |
| GVI/KGVI | HRV | | | 2 | | |
| OELV | IRL | | | 2 | | |
| TLV | NOR | 2 | | | | |
| NDS/NDSch | POL | 0,5 | | 1 | | |
| NGV/KGV | SWE | 1 | | 2 | | INHAL |
| WEL | GBR | | | 2 | | |
| TLV-ACGIH | | | | 2 (C) | | |

Health - Derived no-effect level - DNEL / DMEL

| Route of exposure | Effects on consumers | | | | Effects on workers | | | |
|-------------------|----------------------|----------------|---------------|------------------|--------------------|----------------|---------------|------------------|
| | Acute local | Acute systemic | Chronic local | Chronic systemic | Acute local | Acute systemic | Chronic local | Chronic systemic |
| Inhalation | | | 1 mg/m3 | | | | 1 mg/m3 | |

BENZYL ALCOHOL
Threshold Limit Value

| Type | Country | TWA/8h | | STEL/15min | | Remarks / Observations |
|-----------|---------|--------|------|------------|-------|------------------------|
| | | mg/m3 | ppm | mg/m3 | ppm | |
| TLV | BGR | 5 | | | | |
| MAK | CHE | 22 | 5 | | | SKIN |
| VME/VLE | CHE | 22 | 5 | | | SKIN |
| TLV | CZE | 40 | 9,04 | 80 | 18,08 | |
| AGW | DEU | 22 | 5 | 44 | 10 | SKIN |
| HTP | FIN | 45 | 10 | | | 11 |
| RD | LTU | 5 | | | | SKIN |
| RV | LVA | 5 | | | | |
| NDS/NDSch | POL | 240 | | | | |
| MV | SVN | 22 | 5 | 44 | 10 | SKIN |

B-GTX PULITORE FUGHE
Predicted no-effect concentration - PNEC

| | | |
|--|-----|-------|
| Normal value in fresh water | 1 | mg/l |
| Normal value in marine water | 1 | mg/l |
| Normal value for fresh water sediment | 527 | mg/kg |
| Normal value for marine water sediment | 527 | mg/kg |
| Normal value for water, intermittent release | 23 | mg/l |
| Normal value of STP microorganisms | 39 | mg/l |
| Normal value for the terrestrial compartment | 45 | mg/kg |

Health - Derived no-effect level - DNEL / DMEL

| Route of exposure | Effects on consumers | | | Chronic systemic | Effects on workers | | |
|-------------------|----------------------|----------------|---------------|------------------|--------------------|----------------|---------------|
| | Acute local | Acute systemic | Chronic local | | Acute local | Acute systemic | Chronic local |
| Oral | | 20 mg/kg bw/d | | 4 mg/kg bw/d | | | |
| Inhalation | | 27 mg/m3 | | 5,4 mg/m3 | 110 mg/m3 | | 22 mg/m3 |
| Skin | | 20 mg/kg bw/d | | 4 mg/kg bw/d | 40 mg/kg bw/d | | 8 mg/kg bw/d |

SODIUM METASILICATE PENTAHYDRATE
Predicted no-effect concentration - PNEC

| | | |
|--|------|------|
| Normal value in fresh water | 75 | mg/l |
| Normal value in marine water | 1 | mg/l |
| Normal value for water, intermittent release | 75 | mg/l |
| Normal value of STP microorganisms | 1000 | mg/l |

Health - Derived no-effect level - DNEL / DMEL

| Route of exposure | Effects on consumers | | | Chronic systemic | Effects on workers | | |
|-------------------|----------------------|----------------|---------------|------------------|--------------------|----------------|-----------------|
| | Acute local | Acute systemic | Chronic local | | Acute local | Acute systemic | Chronic local |
| Oral | | | | 0.74 mg/kg bw/d | | | |
| Inhalation | | | | 1.55 mg/m3 | | | 6.22 mg/m3 |
| Skin | | | | 0.74 mg/kg bw/d | | | 1.49 mg/kg bw/d |

SODIUM P-CUMENESULPHONATE
Predicted no-effect concentration - PNEC

| | | |
|--|-----|------|
| Normal value in fresh water | 23 | mg/l |
| Normal value for water, intermittent release | 23 | mg/l |
| Normal value of STP microorganisms | 100 | mg/l |

Health - Derived no-effect level - DNEL / DMEL

| Route of exposure | Effects on consumers | | | Chronic systemic | Effects on workers | | |
|-------------------|----------------------|----------------|---------------|------------------|--------------------|----------------|----------------|
| | Acute local | Acute systemic | Chronic local | | Acute local | Acute systemic | Chronic local |
| Oral | | | | | | | 3.8 mg/kg bw/d |
| Inhalation | | | | 13.2 mg/m3 | | | 53.6 mg/m3 |
| Skin | | | | 3.8 mg/kg bw/d | | | 7.6 mg/kg bw/d |

**B-GTX PULITORE FUGHE****SULFURIC ACID, MONO-C12-14-ALKYL ESTERS, SODIUM SALTS**

Predicted no-effect concentration - PNEC

| | | |
|--|-----|-------|
| Normal value in fresh water | 131 | mg/l |
| Normal value in marine water | 13 | mg/l |
| Normal value for marine water sediment | 461 | mg/kg |
| Normal value for the terrestrial compartment | 846 | mg/kg |

Health - Derived no-effect level - DNEL / DMEL

| Route of exposure | Effects on consumers | | | Effects on workers | | | | |
|-------------------|----------------------|----------------|---------------|--------------------|-------------|----------------|---------------|------------------|
| | Acute local | Acute systemic | Chronic local | Chronic systemic | Acute local | Acute systemic | Chronic local | Chronic systemic |
| Oral | | | | 24 mg/kg bw/d | | | | |
| Inhalation | | | | 85 mg/m3 | | | | 285 mg/m3 |
| Skin | | | | 2440 mg/kg bw/d | | | | 4060 mg/kg bw/d |

Legend:
(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.
VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.
Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category III professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear a hood visor or protective visor combined with airtight goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

B-GTX PULITORE FUGHE**SECTION 9. Physical and chemical properties****9.1. Information on basic physical and chemical properties**

| Properties | Value | Information |
|--|-------------------------------|---|
| Appearance | liquid | Method:visual |
| Colour | yellow | |
| Odour | solvent | Method:own |
| Odour threshold | not available | |
| Odour threshold | not available | Concentration: 0,1 – 0,48 % Substance:2-BUTOXYETHANOL |
| Melting point / freezing point | < -5 °C | Method:own |
| Initial boiling point | 171 °C | Substance:2-BUTOXYETHANOL |
| Flammability | not flammable | Remark:it does not contain substances classified as flammable |
| Lower explosive limit | not available | Concentration: 1,3 % Substance:2-BUTOXYETHANOL |
| Upper explosive limit | not available | Concentration: 10,6 % Substance:2-BUTOXYETHANOL |
| Flash point | > 60 °C | Remark:it does not contain substances classified as flammable |
| Auto-ignition temperature | 230 °C | Substance:2-BUTOXYETHANOL |
| Decomposition temperature | not available | |
| pH | 13,00 ± 0,50 | Method:own instrument: METTLER TOLEDO SEVEN GO electrode: METTLER TOLEDO InLab 413 SG / 2m IP67 |
| Kinematic viscosity | 5,0 mm ² /s | Method:Calculation |
| Dynamic viscosity | 5,0 cP | Method:BROOKFIELD DV1 LV (spindle=1 / speed=100 / T=20°C) |
| Solubility | soluble in water in any ratio | Method:own |
| Partition coefficient: n-octanol/water | not available | Reason for missing data:The product is a blend |
| Vapour pressure | 17,2 mmHg | Method:calculation |
| Density and/or relative density | 1,02 - 1,07 g/cm ³ | Method:Own Instrument: METTLER TOLEDO DENSITOPRO Substance:2-BUTOXYETHANOL |
| Relative vapour density | 4,1 | |
| Particle characteristics | not applicable | |

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

| | | |
|----------------------------|------------------------|---|
| VOC (Directive 2010/75/EU) | 5,08 % - 52,83 g/litre | |
| VOC (volatile carbon) | 3,10 % - 32,23 g/litre | |
| Explosive properties | not explosive | Remark:it does not contain substances classified as explosive |
| Oxidising properties | not oxidizing | Remark:it does not contain substances classified as oxidizing |

B-GTX PULITORE FUGHE**SECTION 10. Stability and reactivity****10.1. Reactivity**

Corrode: aluminum, zinc, tin, aluminum alloys, zinc alloys, tin alloys.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

In contact with hot trichlorethylene or tetrachlorethylene it forms derivatives of chloroacetylene which are flammable and explosive in contact with air as well as extremely toxic. Reacts violently with danger of explosions with nitro derivatives, phosphorus and with chloroform and methanol. It can generate explosive gases in contact with tetrahydrofuran. It gives an exothermic reaction with acids and in general with all halogenated compounds

10.4. Conditions to avoid

Avoid exposure to: heat sources, open flames. Keep separate from: oxidizing agents, acids, flammable substances, halogens, organic substances. Keep away from: lead, aluminum, copper, tin, sulfur, bronze.

10.5. Incompatible materials

Avoid contact with: zinc, tin, copper and their alloys, sulfuric acid, oxidizing substances, strong acids

10.6. Hazardous decomposition products

Carbon oxides

SECTION 11. Toxicological information**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

B-GTX PULITORE FUGHEACUTE TOXICITY

ATE (Inhalation - vapours) of the mixture: > 20 mg/l
ATE (Oral) of the mixture: >2000 mg/kg
ATE (Dermal) of the mixture: Not classified (no significant component)

2-BUTOXYETHANOL

LD50 (Dermal): > 2000 mg/kg bw/day ratto (OECD 402)
LD50 (Oral): 1200 mg/kg bw/day ratto maschio (OCSE 401)
LC50 (Inhalation vapours): 3 mg/l/4h Rat
STA (Inhalation vapours): 11 mg/l estimate from table 3.1.2 of Annex I of the CLP
(figure used for calculation of the acute toxicity estimate of the mixture)

POTASSIUM HYDROXIDE

LD50 (Oral): 333 mg/kg Rat

BENZYL ALCOHOL

LD50 (Dermal): 2000 mg/kg coniglio
LD50 (Oral): 1620 mg/kg ratto (maschio)
LC50 (Inhalation vapours): > 4178 mg/l/4h ratto (OCSE 403)
STA (Inhalation vapours): 11 mg/l estimate from table 3.1.2 of Annex I of the CLP
(figure used for calculation of the acute toxicity estimate of the mixture)

SODIUM METASILICATE PENTAHYDRATE

LD50 (Dermal): > 5000 mg/kg/bw ratto
LD50 (Oral): 1152 mg/kg ratto
LC50 (Inhalation vapours): > 206 g/m3 ratto

SODIUM P-CUMENESULPHONATE

LD50 (Dermal): > 2000 mg/kg coniglio
LD50 (Oral): > 7000 mg/kg ratto
LC50 (Inhalation vapours): > 641 mg/l/4h ratto

SKIN CORROSION / IRRITATION

Corrosive for the skin

Classification according to the experimental pH value

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

B-GTX PULITORE FUGHEGERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information**12.1. Toxicity****BENZYL ALCOHOL**

| | |
|-----------------------------------|---|
| LC50 - for Fish | 460 mg/l/96h Pimephales promelas |
| EC50 - for Crustacea | 230 mg/l/48h Daphnia magna (OCSE 202) |
| EC50 - for Algae / Aquatic Plants | 770 mg/l/72h Pseudokirchneriella subcapitata (OCSE 201) |
| Chronic NOEC for Crustacea | 51 mg/l 21d Daphnia magna (OCSE 211) |

SODIUM METASILICATE PENTAHYDRATE

| | |
|----------------------|--------------------------------|
| LC50 - for Fish | 210 mg/l/96h brachydanio rerio |
| EC50 - for Crustacea | 1700 mg/l/48h Daphnia magna |

2-BUTOXYETHANOL

| | |
|-----------------------------------|---|
| LC50 - for Fish | 1474 mg/l/96h Oncorhynchus mykiss (OECD 203) |
| EC50 - for Crustacea | 1550 mg/l/48h Daphnia magna (OECD 202) |
| EC50 - for Algae / Aquatic Plants | 911 mg/l/72h Pseudokirchneriella subcapitata (OECD 201) |
| Chronic NOEC for Fish | > 100 mg/l 21d Brachydanio rerio (OECD 204) |

B-GTX PULITORE FUGHE**POTASSIUM HYDROXIDE**

LC50 - for Fish

80 mg/l/96h *Gambusia affinis***SODIUM P-CUMENESULPHONATE**

LC50 - for Fish

1000 mg/l/96h *Oncorhynchus mykiss* (EPA OTS 797.1400)

EC50 - for Crustacea

1000 mg/l/48h *Daphnia Magna* (EPA OTS 797.1300)

EC50 - for Algae / Aquatic Plants

> 230 mg/l/96h *Selenastrum capricornutum* (EPA OTS 797.1050)

Chronic NOEC for Algae / Aquatic Plants

31 mg/l/96h *Selenastrum capricornutum* (EPA OTS 797.1050)**12.2. Persistence and degradability****BENZYL ALCOHOL**

Rapidly degradable

SODIUM METASILICATE PENTAHYDRATE

Rapidly degradable

2-BUTOXYETHANOL

Rapidly degradable

POTASSIUM HYDROXIDE

Solubility in water

> 10000 mg/l

Degradability: information not available

SODIUM P-CUMENESULPHONATE

Rapidly degradable

12.3. Bioaccumulative potential**BENZYL ALCOHOL**

Partition coefficient: n-octanol/water

1,05

2-BUTOXYETHANOL

Partition coefficient: n-octanol/water

0,81

SODIUM P-CUMENESULPHONATE

Partition coefficient: n-octanol/water

-3,12

BCF

< 2,3

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessmentOn the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.**12.6. Endocrine disrupting properties**

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

B-GTX PULITORE FUGHE**12.7. Other adverse effects**

Information not available

SECTION 13. Disposal considerations**13.1. Waste treatment methods**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information**14.1. UN number or ID number**

ADR / RID, IMDG, IATA: 1719

14.2. UN proper shipping name

ADR / RID: CAUSTIC ALKALI LIQUID, N.O.S. (POTASSIUM HYDROXIDE; SODIUM METASILICATE PENTAHYDRATE)

IMDG: CAUSTIC ALKALI LIQUID, N.O.S. (POTASSIUM HYDROXIDE; SODIUM METASILICATE PENTAHYDRATE)

IATA: CAUSTIC ALKALI LIQUID, N.O.S. (POTASSIUM HYDROXIDE; SODIUM METASILICATE PENTAHYDRATE)

14.3. Transport hazard class(es)

ADR / RID: Class: 8 Label: 8

IMDG: Class: 8 Label: 8

IATA: Class: 8 Label: 8

**14.4. Packing group**

ADR / RID, IMDG, IATA: II

14.5. Environmental hazards

ADR / RID: NO

IMDG: NO

IATA: NO



14.6. Special precautions for user

| | | | |
|------------|---------------------------------------|-------------------------|------------------------------|
| ADR / RID: | HIN - Kemler: 80 | Limited Quantities: 1 L | Tunnel restriction code: (E) |
| IMDG: | Special provision: - EMS: F-A, S-B | Limited Quantities: 1 L | |
| IATA: | Cargo: | Maximum quantity: 30 L | Packaging instructions: 855 |
| | Pass.: | Maximum quantity: 1 L | Packaging instructions: 851 |
| | Special provision: | A3, A803 | |

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 3

Contained substance

Point 75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage \geq than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

B-GTX PULITORE FUGHESubstances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

Regulation (EC) No. 648/2004

Ingredients according to Regulation (EC) No. 648/2004

The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No. 648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

| | |
|----------------------|--|
| Met. Corr. 1 | Substance or mixture corrosive to metals, category 1 |
| Acute Tox. 4 | Acute toxicity, category 4 |
| Skin Corr. 1A | Skin corrosion, category 1A |
| Skin Corr. 1B | Skin corrosion, category 1B |
| Eye Dam. 1 | Serious eye damage, category 1 |
| Eye Irrit. 2 | Eye irritation, category 2 |
| Skin Irrit. 2 | Skin irritation, category 2 |
| STOT SE 3 | Specific target organ toxicity - single exposure, category 3 |
| H290 | May be corrosive to metals. |
| H302 | Harmful if swallowed. |
| H332 | Harmful if inhaled. |
| H314 | Causes severe skin burns and eye damage. |
| H318 | Causes serious eye damage. |
| H319 | Causes serious eye irritation. |
| H315 | Causes skin irritation. |
| H335 | May cause respiratory irritation. |
| EUH210 | Safety data sheet available on request. |

B-GTX PULITORE FUGHE

Use descriptor system:

| | | |
|-------------|-----------|---|
| ERC | 8a | Widespread use of non- reactive processing aid (no inclusion into or onto article, indoor) |
| ERC | 8d | Widespread use of non- reactive processing aid (no inclusion into or onto article, outdoor) |
| LCS | C | Consumer use |
| LCS | PW | Widespread use by professional workers |
| PC | 35 | Washing and cleaning products |
| PROC | 11 | Non industrial spraying |

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)



BELLINZONI S.R.L.

Revision nr. 1

Dated 12/12/2022

Printed on 12/12/2022

Page n. 20/23

B-GTX PULITORE FUGHE

- 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
- 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
- 22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

B-GTX PULITORE FUGHE

SUMI
Safe Use of Mixtures
Information**AISE_SUMI_PW_11_2_G**

Version 1.1, August 2018

Professional uses; (Trigger) spraying

This document is intended to communicate the conditions of safe use for the product and should always be read in combination with the product's Safety Data Sheet and labels.

General description of the process covered

This SUMI applies to professional uses of products in a spraying application. This Safe Use Information is based on the AISE_SWED_PW_11_2.

Operational Conditions

| | |
|--|---|
| Maximum duration | 60 minutes per day. |
| Range of application / Process conditions | Indoor use |
| | Process carried out at room temperature. |
| | In case of dilution, tap water at a maximum temperature of 45°C is used. |
| Air exchange rate | Provide a basic standard of general ventilation (1 to 3 air changes per hour). No LEV required. |

Risk Management Measures

| | |
|---|---|
| Measures related to personal protective equipment (PPE), hygiene and health evaluation | Wear suitable gloves and eye protection. See section 8 of the SDS of this product for specifications.  |
| | Training of workers in relation to proper use and maintenance of PPEs must be ensured. |
| Environmental measures | Prevent that undiluted product reaches surface waters. |
| | If appropriate AISE SPERC 8a.1.a.v2 may apply: wide dispersive use resulting in release to municipal sewage treatment plant. |

| | | |
|---|-----------------------------|--|
|  | BELLINZONI S.R.L. | Revision nr. 1 Dated 12/12/2022 Printed on 12/12/2022 Page n. 22/23 |
| | B-GTX PULITORE FUGHE | |

Additional good practice advice

| | |
|---|---|
| Don't eat or drink. Don't smoke. Don't use in proximity of open flame. |  |
| Wash hands after use. Avoid contact with damaged skin. Do not mix with other products. |  |
| Spillage instructions | Dilute with fresh water and mop up. |
| Hygiene practices | Follow the product instructions as specified on the label or in the product information sheet and use good occupational hygiene practices as specified in Section 7 of the product SDS. |

Additional information depending on product composition

The label and (when required) the Safety Data Sheet contain additional, product specific information crucial for working safely with mixtures. Please refer to the product label and SDS for information including, but not limited to: product hazard classification, potentially allergenic fragrances, notable ingredients and threshold limit values (when available).

Disclaimer

This is a document for communicating generic conditions of safe use of a product. It is the responsibility of the formulator to link this SUMI to the SDS of a specific product that he is selling. If a SUMI (or associated SWED) code is mentioned in the SDS of a product, the formulator of that product declares that all substances in the mixture are present in such concentration, that the use of the product within the conditions of the SUMI is safe. When available, this safe use is ensured by evaluating the results of the chemical safety assessments as performed by the raw material suppliers. When no chemical safety assessment has been carried out by the supplier for an ingredient that contributes to the classification of the mixture, the formulator has performed a safety assessment himself. Following Occupational Health legislation, the employer of workers that use products that are assessed as safe following SUMI conditions remains responsible for communicating relevant use information to employees. When developing workplace instructions for employees, SUMI Sheets should always be considered in combination with the SDS and the label of the product. This document is provided by A.I.S.E. for general information purposes only. The formulator uses the content of this document at its sole risk. A.I.S.E. disclaims any liability to any person or entity for any loss, damage no matter of what kind (actual, consequential, punitive or otherwise), injury, claim, liability or other cause of any kind or character based upon or resulting from the use (even partly) of the content of this document.



BELLINZONI S.R.L.

Revision nr. 1

Dated 12/12/2022

Printed on 12/12/2022

Page n. 23/23

B-GTX PULITORE FUGHE

WORKING INSTRUCTIONS SHEET

The purpose of this sheet is to provide the personnel carrying out the cleaning operations with instructions for an appropriate and safe use of the products and for the correct management of emergency situations.

| | |
|--|--|
| Operation planned | Non industrial spraying [PROC11] |
| Product name | B-GTX PULITORE FUGHE |
| Risks of the product as it is | H290 May be corrosive to metals. H314 Causes severe skin burns and eye damage. |
| Handling of the product as it is | Ensure an adequate earthing system for plants and people. Avoid contact with eyes and skin. Do not inhale any dusts or vapors or mists. Do not eat, drink or smoke during use. Wash hands after use. Avoid the dispersion of the product in the environment |
| PPE required For product as it is | Protect hands with category III work gloves (see standard EN 374). Wear category III professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wear a hood visor or protective visor combined with airtight goggles (see standard EN 166). |
| In case of emergency (accidents involving exposure to the product) | Inform the client immediately. Immediately notify the employer. Contact the Anti-Poison Center listed in section 1.4 of the SDS |
| In case of accidental spillage of large quantities of the product as it is | Wear adequate protective equipment (including personal protective equipment referred to in section 8 of the SDS) to prevent contamination of skin, eyes and personal clothing. Suck up the leaked product into a suitable container. Evaluate the compatibility of the container to be used with the product, checking the sect. 10 of the SDS. Absorb the remainder with inert absorbent material. Provide sufficient ventilation of the place affected by the leak. The disposal of contaminated material must be carried out in accordance with the provisions of section 13 of the SDS |
| Product storage | Keep only in the original container. Store in a ventilated place, away from sources of ignition. Keep containers tightly closed. Keep the product in clearly labeled containers. Avoid overheating. Avoid violent shocks. Keep containers away from any incompatible materials, checking section 10. |
| In case of accidents, emergencies or fire in the work area | Immediately notify the client, the employer. Follow the instructions for emergencies. Follow the instructions in sect. 5 of the SDS |