

**BELLINZONI S.R.L.**

Revision nr. 2

Dated 27/02/2023

Printed on 27/02/2023

Page n. 1/19

Replaced revision:1 (Printed on: 18/01/2021)

**EPOX PREMIUM TRASPARENTE VERTICALE
COMPONENTE B**

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: 019METVPRB - 019METVPRB0005
Product name: EPOX PREMIUM TRASPARENTE VERTICALE COMPONENTE B
UFI : ENA0-Q0RC-Q00H-P4KP

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: Catalyst for epoxy resins

Identified Uses	Industrial	Professional	Consumer
Catalyst	-	PC: 1. LCS: PW.	-

1.3. Details of the supplier of the safety data sheet

Name: BELLINZONI S.R.L.
Full address: Via Mezzano 64
District and Country: 28069 Trecate (NO)
Italia
Tel. +39 0321 770558

e-mail address of the competent person

responsible for the Safety Data Sheet
Supplier:

laboratorio@bellinzoni.com
BELLINZONI S.r.l.

1.4. Emergency telephone number

For urgent inquiries refer to

- CAV "Osp. Pediatrico Bambino Gesù" Dip. Emergenza e Accettazione DEA – Roma - Piazza Sant'Onofrio, 4 CAP: 00165 – Telefono: 06 68593726 – Responsabile: Marco Marano
- Az. Osp. Univ. Foggia – Foggia - V.le Luigi Pinto, 1 – CAP: 71122 – Telefono: 800183459 – Responsabile: Anna Lepore
- Az. Osp. "A. Cardarelli" – Napoli - Via A. Cardarelli, 9 – CAP: 80131081- Telefono: 5453333 – Responsabile: Romolo Villani
- CAV Policlinico "Umberto I" - Roma - V.le del Policlinico, 155 – CAP: 161 – Telefono: 06-49978000 – Responsabile: M. Caterina Grassi
- CAV Policlinico "A. Gemelli" - Roma - Largo Agostino Gemelli, 8 – CAP: 168 – Telefono: 06-3054343 – Responsabile: Alessandro Barelli
- Az. Osp. "Careggi" U.O. Tossicologia Medica – Firenze - Largo Brambilla, 3 – CAP: 50134 – Telefono: 055-7947819 – Responsabile: Francesco Gambassi
- CAV Centro Nazionale di Informazione Tossicologica - Pavia – Via Salvatore Maugeri, 10 – CAP: 27100 - Telefono: 0382-24444 – Responsabile: Carlo Locatelli
- Osp. Niguarda Ca' Granda – Milano - Piazza Ospedale Maggiore, 3 – CAP: 20162 – Telefono: 02-66101029 – Responsabile: Franca Davanzo
- Azienda Ospedaliera Papa Giovanni XXII – Bergamo - Piazza OMS, 1 – CAP: 24127 – Telefono: 800883300 – Responsabile: Bacis Giuseppe
- Azienda Ospedaliera Integrata Verona – Verona - Piazzale Aristide Stefani, 1 – CAP: 37126 – Telefono: 800011858

**EPOX PREMIUM TRASPARENTE VERTICALE
COMPONENTE B****SECTION 2. Hazards identification****2.1. Classification of the substance or mixture**

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Acute toxicity, category 4	H302	Harmful if swallowed.
Skin corrosion, category 1A	H314	Causes severe skin burns and eye damage.
Serious eye damage, category 1	H318	Causes serious eye damage.
Skin sensitization, category 1	H317	May cause an allergic skin reaction.
Hazardous to the aquatic environment, chronic toxicity, category 3	H412	Harmful to aquatic life with long lasting effects.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: Danger

Hazard statements:

H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H412	Harmful to aquatic life with long lasting effects.
EUH205	Contains epoxy constituents. May produce an allergic reaction.
EUH210	Safety data sheet available on request.

Precautionary
statements:

P260	Do not breathe vapours
P273	Avoid release to the environment.
P280	Wear protective gloves/ protective clothing / eye protection / face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER / doctor

Contains: 1,3-CYCLOHEXANEDIMETHANAMINE
2,2'-[(1-METHYLETHYLIDENE)BIS(4,1-PHENYLENEOXYMETHYLENE)]BISOXIRANE
BENZYL ALCOHOL

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage $\geq$ than 0,1%.
The product does not contain substances with endocrine disrupting properties in concentration $\geq$ 0.1%.

	BELLINZONI S.R.L.	Revision nr. 2
	EPOX PREMIUM TRASPARENTE VERTICALE COMPONENTE B	Dated 27/02/2023 Printed on 27/02/2023 Page n. 3/19 Replaced revision:1 (Printed on: 18/01/2021)

SECTION 3. Composition/information on ingredients

3.1. Substances

Information not relevant

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
1,3-CYCLOHEXANEDIMETHANAMINE		
INDEX -	$45 \leq x < 50$	Acute Tox. 4 H302, Acute Tox. 4 H312, Skin Corr. 1 H314, Eye Dam. 1 H318, Aquatic Chronic 3 H412 LD50 Oral: 700 mg/kg, LD50 Dermal: 1700 mg/kg
EC 219-941-5		
CAS 2579-20-6		
REACH Reg. 01-2119543741-41		
2,2'-[(1-METHYLETHYLIDENE)BIS(4,1-PHENYLENEOXYMETHYLENE)]BIS OXIRANE		
INDEX 603-073-00-2	$19 \leq x < 22$	Eye Irrit. 2 H319, Skin Irrit. 2 H315, Skin Sens. 1 H317, Aquatic Chronic 2 H411 Skin Irrit. 2 H315: $\geq 5\%$, Eye Irrit. 2 H319: $\geq 5\%$
EC 216-823-5		
CAS 1675-54-3		
REACH Reg. 01-2119456619-26		
BENZYL ALCOHOL		
INDEX 603-057-00-5	$19 \leq x < 22$	Acute Tox. 4 H302, Acute Tox. 4 H332, Eye Irrit. 2 H319 LD50 Oral: 1620 mg/kg, STA Inhalation vapours: 11 mg/l
EC 202-859-9		
CAS 100-51-6		
REACH Reg. 01-2119492630-38		
ETHANEDIOL		
INDEX 603-027-00-1	$0,4 \leq x < 0,55$	Acute Tox. 4 H302, STOT RE 2 H373 STA Oral: 500 mg/kg
EC 203-473-3		
CAS 107-21-1		
REACH Reg. 01-2119456816-28		

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

	BELLINZONI S.R.L.	Revision nr. 2
	EPOX PREMIUM TRASPARENTE VERTICALE COMPONENTE B	Dated 27/02/2023 Printed on 27/02/2023 Page n. 4/19 Replaced revision:1 (Printed on: 18/01/2021)

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

	BELLINZONI S.R.L.	Revision nr. 2
	EPOX PREMIUM TRASPARENTE VERTICALE COMPONENTE B	Dated 27/02/2023 Printed on 27/02/2023 Page n. 5/19 Replaced revision:1 (Printed on: 18/01/2021)

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

AUS	Österreich	Gesamte Rechtsvorschrift für Grenzwerteverordnung 2021 , Fassung vom 17.06.2021
BEL	Belgique	Liste de valeurs limites d'exposition aux agents chimiques, livre VI du code du bien-être au travail
BGR	България	НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г. ЗА ЗАЩИТА НА РАБОТЕЩИТЕ ОТ РИСКОВЕ, СВЪРЗАНИ С ЕКСПОЗИЦИЯ НА ХИМИЧНИ АГЕНТИ ПРИ РАБОТА (изм. ДВ. бр.5 от 17 Януари 2020г.)
CHE	Suisse / Schweiz	Valeurs limites d'exposition aux postes de travail: VME/VLE (SUVA). Grenzwerte am Arbeitsplatz: MAK (SUVA)
CYP	Κύπρος	Οι πεπτά Αζθάλειαρ και Υγείαρ ζηην Δπγαζία (Φημικοί Παπάγονηερ) (Τποποποιηηκοί) Κανονίζμοι ηος 2019. Οι περί Ασφάλειας και Υγείας στην Εργασία (Καρκινογόνοι και Μεταλλαξιογόνοι Παράγοντες) (Τροποποιηηκοί) Κανονισμοί του 2020
CZE	Česká Republika	Nařízení vlády č. 41/2020 Sb. Nařízení vlády, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci, ve znění pozdějších předpisů
DEU	Deutschland	Technischen Regeln für Gefahrstoffe (TRGS 900) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte. MAK- und BAT-Werte-Liste 2020, Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe, Mitteilung 56
DNK	Danmark	Bekendtgørelse om grænseværdier for stoffer og materialer - BEK nr 1458 af 13/12/2019
ESP	España	Límites de exposición profesional para agentes químicos en España 2021
EST	Eesti	Ohtlike kemikaalide ja neid sisaldavate materjalide kasutamise töötervishoiu ja tööohutuse nõuded ning töökeskonna keemiliste ohtegurite piirnormid [RT I, 17.10.2019, 1 - jõust. 17.01.2020]
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
FIN	Suomi	HTP-VÄRDEN 2020. Koncentrationer som befunnits skadliga. SOCIAL - OCH HÄLSOVÄRDSMINISTERIETS PUBLIKATIONER 2020:25
GRC	Ελλάδα	Π.Δ. 26/2020 (ΦΕΚ 50/Α' 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ ``σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξιγόνους παράγοντες κατά την εργασία``»
HUN	Magyarország	Az innovációért és technológiáért felelős miniszter 5/2020. (II. 6.) ITM rendelete a kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
HRV	Hrvatska	Pravilnik o izmjenama i dopunama Pravilnika o zaštiti radnika od izloženosti opasnim kemikalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 1/2021)
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
IRL	Éire	2020 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations (2001-2015) and the Safety, Health and Welfare at Work (Carcinogens) Regulations (2001-2019)
LUX	Luxembourg	Règlement grand-ducal du 24 janvier 2020 modifiant le règlement grand-ducal du 14 novembre 2016 concernant la protection des salariés contre les risques liés à l'exposition à des agents cancérigènes ou mutagènes au travail
LTU	Lietuva	Jsakymas dėl lietuvis higienos normos hn 23:2011 „cheminių medžiagų profesinio poveikio ribiniai dydžiai. Matavimo ir poveikio vertinimo bendrieji reikalavimai“ patvirtinimo
LVA	Latvija	Grozījumi Ministru kabineta 2007. gada 15. maija noteikumos Nr. 325 "Darba aizsardzības prasības saskarē ar ķīmiskajām vielām darba vietās" (prot. Nr. 32 18. §; prot. Nr. 1 22. §)

	BELLINZONI S.R.L.	Revision nr. 2
	EPOX PREMIUM TRASPARENTE VERTICALE COMPONENTE B	Dated 27/02/2023 Printed on 27/02/2023 Page n. 6/19 Replaced revision:1 (Printed on: 18/01/2021)

MLT	Malta	PROTECTION OF THE HEALTH AND SAFETY OF WORKERS FROM THE RISKS RELATED TO CHEMICAL AGENTS AT WORK REGULATIONS (S.L.424.24). PROTECTION OF WORKERS FROM THE RISKS RELATED TO EXPOSURE TO CARCINOGENS OR MUTAGENS AT WORK REGULATIONS (S.L.424.22)
NOR	Norge	Forskrift om endring i forskrift om tiltaksverdier og grenseverdier for fysiske og kjemiske faktorer i arbeidsmiljøet samt smitterisikogrupper for biologiske faktorer (forskrift om tiltaks- og grenseverdier), 21. august 2018 nr. 1255
NLD	Nederland	Arbeidsomstandighedenregeling. Lijst van wettelijke grenswaarden op grond van de artikelen 4.3, eerste lid, en 4.16, eerste lid, van het Arbeidsomstandighedenbesluit
PRT	Portugal	Decreto-Lei n.º 1/2021 de 6 de janeiro, valores-limite de exposição profissional indicativos para os agentes químicos. Decreto-Lei n.º 35/2020 de 13 de julho, proteção dos trabalhadores contra os riscos ligados à exposição durante o trabalho a agentes cancerígenos ou mutagénicos
POL	Polska	Rozporządzenie ministra rozwoju, pracy i technologii z dnia 18 lutego 2021 r. Zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w środowisku pracy
ROU	România	Hotărârea nr. 53/2021 pentru modificarea hotărârii guvernului nr. 1.218/2006, precum și pentru modificarea și completarea hotărârii guvernului nr. 1.093/2006
SWE	Sverige	Hygieniska gränsvärden, Arbetsmiljöverkets föreskrifter och allmänna råd om hygieniska gränsvärden (AFS 2018:1)
SVK	Slovensko	NARIADENIE VLÁDY Slovenskej republiky z 12. augusta 2020, ktorým sa mení a dopĺňa nariadenie vlády Slovenskej republiky č. 356/2006 Z. z. o ochrane zdravia zamestnancov pred rizikami súvisiacimi s expozíciou karcinogénnym a mutagénnym faktorom pri práci v znení neskorších predpisov
SVN	Slovenija	Pravilnik o varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu (Uradni list RS, št. 100/01, 39/05, 53/07, 102/10, 43/11 – ZVZD-1, 38/15, 78/18 in 78/19)
TUR	Türkiye	Kimyasal Maddelerle Çalışmalarda Sağlık ve Güvenlik Önlemleri Hakkında Yönetmelik 12.08.2013 / 28733
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
EU	OEL EU	Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2022

1,3-CYCLOHEXANEDIMETHANAMINE								
Predicted no-effect concentration - PNEC								
Normal value in fresh water			0,0331		mg/l			
Normal value in marine water			0,00331		mg/l			
Normal value for fresh water sediment			0,218		mg/kg dw			
Normal value for marine water sediment			0,0218		mg/kg dw			
Normal value for water, intermittent release			0,331		mg/l			
Normal value of STP microorganisms			10		mg/l			
Normal value for the terrestrial compartment			0,0241		mg/kg dw			
Health - Derived no-effect level - DNEL / DMEL								
Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation							0,00947 mg/m3	
Skin						0,0252 mg/kg bw/d		0,1 mg/kg bw/d

2,2'-[(1-METHYLETHYLIDENE)BIS(4,1-PHENYLENEOXYMETHYLENE)]BISOXIRANE								
Predicted no-effect concentration - PNEC								
Normal value in fresh water				0,0006	mg/l			
Normal value in marine water				0,00006	mg/l			
Normal value for fresh water sediment				0,341	mg/kg/d			
Normal value for marine water sediment				0,0341	mg/kg/d			
Normal value for marine water, intermittent release				0,0018	mg/l			

	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		20 mg/kg bw/d		4 mg/kg bw/d				
Inhalation		27 mg/m3		5,4 mg/m3		110 mg/m3		22 mg/m3
Skin		20 mg/kg bw/d		4 mg/kg bw/d		40 mg/kg bw/d		8 mg/kg bw/d

ETHANEDIOL							
Threshold Limit Value							
Type	Country	TWA/8h		STEL/15min		Remarks / Observations	
		mg/m3	ppm	mg/m3	ppm		
MAK	AUS	26	10	52	20	SKIN	STEL:5(Mow), Häufigkeit/Sch:8x
VLEP	BEL	52	20	104 (C)	40 (C)	SKIN	
TLV	BGR	52	20	104	40	SKIN	
MAK	CHE	26	10	52	20	SKIN	
VME/VLE	CHE	26	10	52	20	SKIN	
TLV	CYP	52	20	104	40	SKIN	
TLV	CZE	50	19,4	100	38,8	SKIN	
AGW	DEU	26	10	52	20	SKIN	
MAK	DEU	26	10	52	20	SKIN	
TLV	DNK	26	10			SKIN	E
VLA	ESP	52	20	104	40	SKIN	
TLV	EST	52	20	104	40	SKIN	
VLEP	FRA	52	20	104	40	SKIN	
HTP	FIN	50	20	100	40	SKIN	
TLV	GRC	125	50	125	50		
AK	HUN	52		104		SKIN	
GVI/KGVI	HRV	52	20	104	40	SKIN	
VLEP	ITA	52	20	104	40	SKIN	
OELV	IRL	10				SKIN	Particulates
VL	LUX	52	20	104	40	SKIN	
RD	LTU	25	10	50	20	SKIN	
RV	LVA	52	20	104	40	SKIN	
TLV	MLT	52	20	104	40	SKIN	
TLV	NOR	52	20			SKIN	
TGG	NLD	52		104		SKIN	
VLE	PRT	52	20	104	40	SKIN	
NDS/NDSCh	POL	15		50		SKIN	
TLV	ROU	52	20	104	40	SKIN	
NGV/KGV	SWE	25	10	104	40	SKIN	
NPEL	SVK	52	20	104	40	SKIN	
MV	SVN	52	20	104	40	SKIN	
ESD	TUR	52	20	104	40	SKIN	
WEL	GBR	52	20	104	40	SKIN	
OEL	EU	52	20	104	40	SKIN	
TLV-ACGIH			25		50		
TLV-ACGIH				10		INHAL	

	BELLINZONI S.R.L.	Revision nr. 2
	EPOX PREMIUM TRASPARENTE VERTICALE COMPONENTE B	Dated 27/02/2023 Printed on 27/02/2023 Page n. 9/19 Replaced revision:1 (Printed on: 18/01/2021)

Predicted no-effect concentration - PNEC		
Normal value in fresh water	10	mg/l
Normal value in marine water	1	mg/l
Normal value for fresh water sediment	37	mg/kg
Normal value for marine water sediment	3,7	mg/kg
Normal value for water, intermittent release	10	mg/l
Normal value of STP microorganisms	199,5	mg/l
Normal value for the terrestrial compartment	1,53	mg/kg

Health - Derived no-effect level - DNEL / DMEL								
Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation			7 mg/m3				35 mg/m3	
Skin				53 mg/kg bw/d				106 mg/kg bw/d

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ;

MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Nitrile gloves according to EN374 class 6 (B-F-I) permeation time > 480 minutes

SKIN PROTECTION

Wear clothing that guarantees full skin protection in accordance with EN 14605 Type 4 in case of splashes, e.g. in Tyrek. Please note: the garment must be changed immediately if it comes into contact with the product

EYE PROTECTION

Use closed safety visors or hermetic protective goggles (e.g. EN166 F3), do not use eye lenses.

In the presence of risks of exposure to splashes or squirts during work, adequate mouth, nose and eye protection should be used to prevent accidental absorption.

RESPIRATORY PROTECTION

Use an adequate respiratory protection device, mask with filter "A", brown, for organic gases and vapors with boiling point >65°C.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

	BELLINZONI S.R.L.	Revision nr. 2
	EPOX PREMIUM TRASPARENTE VERTICALE COMPONENTE B	Dated 27/02/2023 Printed on 27/02/2023 Page n. 10/19 Replaced revision:1 (Printed on: 18/01/2021)

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	viscous liquid	
Colour	colourless	
Odour	characteristic	
Melting point / freezing point	not available	
Initial boiling point	205 °C	Substance:BENZYL ALCOHOL
Flammability	not available	
Lower explosive limit	not available	Concentration: 1,3 % Substance:BENZYL ALCOHOL
Upper explosive limit	not available	Concentration: 13 % Substance:BENZYL ALCOHOL
Flash point	100 °C	Substance:BENZYL ALCOHOL
Auto-ignition temperature	316 °C	Substance:1,3-CYCLOHEXANEDIMETHANAMINE
Decomposition temperature	not available	
pH	not available	Reason for missing data:the mixture is not polar / aprotic
Kinematic viscosity	> 20,5 mm ² /s	Temperature: 40 °C
Solubility	partially soluble in water	
Partition coefficient: n-octanol/water	not available	Reason for missing data:The product is a blend
Vapour pressure	34 Pa	Substance:1,3-CYCLOHEXANEDIMETHANAMINE
Density and/or relative density	1,1 g/cm ³	
Relative vapour density	not available	
Particle characteristics	not applicable	

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

Total solids (250°C / 482°F)	80,65 %	
VOC (Directive 2010/75/EU)	19,85 % - 218,32 g/litre	
VOC (volatile carbon)	15,00 % - 165,00 g/litre	
Explosive properties	not explosive	Remark:it does not contain substances classified as explosive
Oxidising properties	not oxidizing	Remark:it does not contain substances classified as oxidizing



BELLINZONI S.R.L.

Revision nr. 2

Dated 27/02/2023

Printed on 27/02/2023

Page n. 11/19

Replaced revision:1 (Printed on: 18/01/2021)

**EPOX PREMIUM TRASPARENTE VERTICALE
COMPONENTE B**

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

ETHANEDIOL

In the air absorbs moisture. Decomposes at temperatures above 200°C/392°F.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

It can generate flammable gas in contact with elementary metals (alkali and alkaline earth), strong reducing agents.

It can generate toxic gases in contact with oxidizing mineral acids, halogenated organic substances, organic peroxides and hydroperoxides, strong oxidizing agents.

May catch fire on contact with strong oxidizing agents.

ETHANEDIOL

Risk of explosion on contact with: perchloric acid. May react dangerously with: chlorosulphuric acid, sodium hydroxide, sulphuric acid, phosphorus pentasulphide, chromium (III) oxide, chromyl chloride, potassium perchlorate, potassium dichromate, sodium peroxide, aluminium. Forms explosive mixtures with: air.

10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

ETHANEDIOL

Avoid exposure to: sources of heat, naked flames.

10.5. Incompatible materials

Information not available

10.6. Hazardous decomposition products

ETHANEDIOL

May develop: hydroxyacetaldehyde, glyoxal, acetaldehyde, methane, carbon monoxide, hydrogen.

	BELLINZONI S.R.L.	Revision nr. 2
	EPOX PREMIUM TRASPARENTE VERTICALE COMPONENTE B	Dated 27/02/2023 Printed on 27/02/2023 Page n. 12/19 Replaced revision:1 (Printed on: 18/01/2021)

SECTION 11. Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

1,3-CYCLOHEXANEDIMETHANAMINE

If ingested, it causes severe corrosion of the oral cavity and pharynx with the risk of perforation of the esophagus and stomach

ETHANEDIOL

WORKERS: inhalation; contact with the skin.

POPULATION: inhalation of ambient air; contact with the skin of products containing the substance.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

ETHANEDIOL

Ingestion initially stimulates the central nervous system; later replaced by a phase of depression. There may be kidney damage, with anuria and uremia. Over-exposure symptoms are: vomiting, drowsiness, difficulty in breathing, convulsions. The lethal dose for humans is approx. 1.4 ml/kg.

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation - vapours) of the mixture:	> 20 mg/l
ATE (Oral) of the mixture:	1176,35 mg/kg
ATE (Dermal) of the mixture:	>2000 mg/kg

1,3-CYCLOHEXANEDIMETHANAMINE

LD50 (Dermal):	1700 mg/kg rat
LD50 (Oral):	700 mg/kg rat

2,2'-[(1-METHYLETHYLIDENE)BIS(4,1-PHENYLENEOXYMETHYLENE)]BISOXIRANE

LD50 (Dermal):	23000 mg/kg rat
LD50 (Oral):	15000 mg/kg rat

BENZYL ALCOHOL

LD50 (Dermal):	2000 mg/kg coniglio
LD50 (Oral):	1620 mg/kg ratto (maschio)
LC50 (Inhalation vapours):	> 4178 mg/l/4h ratto (OCSE 403)
STA (Inhalation vapours):	11 mg/l estimate from table 3.1.2 of Annex I of the CLP (figure used for calculation of the acute toxicity estimate of the mixture)



BELLINZONI S.R.L.

Revision nr. 2

Dated 27/02/2023

Printed on 27/02/2023

Page n. 13/19

Replaced revision:1 (Printed on: 18/01/2021)

**EPOX PREMIUM TRASPARENTE VERTICALE
COMPONENTE B**

ETHANEDIOL

LD50 (Dermal):	3500 mg/kg mouse
LD50 (Oral):	7712 mg/kg Rat
LC50 (Inhalation vapours):	2500 mg/l/6h rat

SKIN CORROSION / IRRITATION

Corrosive for the skin

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

ETHANEDIOL

Available studies have shown no carcinogenic potential. In a carcinogenicity study lasting two years, carried out by the US National Toxicology Program (NTP), in which ethylene glycol was administered in the feed, "no evidence of carcinogenic activity" in male and female B6C3F1 mice was observed (NTP, 1993).

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

**BELLINZONI S.R.L.**

Revision nr. 2

Dated 27/02/2023

Printed on 27/02/2023

Page n. 14/19

Replaced revision:1 (Printed on: 18/01/2021)

**EPOX PREMIUM TRASPARENTE VERTICALE
COMPONENTE B****SECTION 12. Ecological information**

This product is dangerous for the environment and the aquatic organisms. In the long term, it have negative effects on aquatic environment.

12.1. Toxicity**BENZYL ALCOHOL**

LC50 - for Fish

460 mg/l/96h Pimephales promelas

EC50 - for Crustacea

230 mg/l/48h Daphnia magna (OCSE 202)

EC50 - for Algae / Aquatic Plants

770 mg/l/72h Pseudokirchneriella subcapitata (OCSE 201)

Chronic NOEC for Crustacea

51 mg/l 21d Daphnia magna (OCSE 211)

ETHANEDIOL

LC50 - for Fish

72,86 mg/l/96h freshwater fish

EC50 - for Crustacea

100 mg/l/48h

Chronic NOEC for Fish

15,38 mg/l freshwater fish

Chronic NOEC for Crustacea

8,59 g/l freshwater invertebrates

Chronic NOEC for Algae / Aquatic Plants

100 mg/l freshwater algae

**2,2'-[(1-METHYLETHYLIDENE)BIS(4,1-PHENYLENEOXYMETHYLENE)]BISOXIRAN
E**

LC50 - for Fish

2 mg/l/96h

EC50 - for Crustacea

1,8 mg/l/48h daphnia magna

Chronic NOEC for Crustacea

0,3 mg/l daphnia magna

1,3-CYCLOHEXANEDIMETHANAMINE

LC50 - for Fish

130 mg/l/96h fish

EC50 - for Algae / Aquatic Plants

90 mg/l/72h alghe

12.2. Persistence and degradability**BENZYL ALCOHOL**

Rapidly degradable

ETHANEDIOL

Solubility in water

1000 - 10000 mg/l

Rapidly degradable

**2,2'-[(1-METHYLETHYLIDENE)BIS(4,1-PHENYLENEOXYMETHYLENE)]BISOXIRAN
E**

Solubility in water

6,9 mg/l 20°C

NOT rapidly degradable

	BELLINZONI S.R.L.	Revision nr. 2
	EPOX PREMIUM TRASPARENTE VERTICALE COMPONENTE B	Dated 27/02/2023 Printed on 27/02/2023 Page n. 15/19 Replaced revision:1 (Printed on: 18/01/2021)

1,3-CYCLOHEXANEDIMETHANAMINE

Solubility in water 100 g/l 20°C
NOT rapidly degradable

12.3. Bioaccumulative potential

BENZYL ALCOHOL

Partition coefficient: n-octanol/water 1,05

ETHANEDIOL

Partition coefficient: n-octanol/water -1,36

2,2'-[(1-METHYLETHYLIDENE)BIS(4,1-PHENYLENEOXYMETHYLENE)]BISOXIRAN E

Partition coefficient: n-octanol/water 3,242 Log Kow
BCF 31 l/Kg w/w

1,3-CYCLOHEXANEDIMETHANAMINE

Partition coefficient: n-octanol/water 0,783

12.4. Mobility in soil

2,2'-[(1-METHYLETHYLIDENE)BIS(4,1-PHENYLENEOXYMETHYLENE)]BISOXIRAN E

Partition coefficient: soil/water 2,648

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage $\geq$ than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.



BELLINZONI S.R.L.

Revision nr. 2

Dated 27/02/2023

Printed on 27/02/2023

Page n. 16/19

Replaced revision:1 (Printed on: 18/01/2021)

**EPOX PREMIUM TRASPARENTE VERTICALE
COMPONENTE B**

SECTION 14. Transport information

14.1. UN number or ID number

ADR / RID, IMDG, IATA: 2735

14.2. UN proper shipping name

ADR / RID: AMINES, LIQUID, CORROSIVE, N.O.S. (CYCLOALIPHATIC AMINE)

IMDG: AMINES, LIQUID, CORROSIVE, N.O.S. (CYCLOALIPHATIC AMINE)

IATA: AMINES, LIQUID, CORROSIVE, N.O.S. (CYCLOALIPHATIC AMINE)

14.3. Transport hazard class(es)

ADR / RID: Class: 8 Label: 8

IMDG: Class: 8 Label: 8

IATA: Class: 8 Label: 8



14.4. Packing group

ADR / RID, IMDG, IATA: III

14.5. Environmental hazards

ADR / RID: NO

IMDG: NO

IATA: NO

14.6. Special precautions for user

ADR / RID: HIN - Kemler: 80

Limited
Quantities: 5
L

Tunnel
restriction
code: (E)

Special provision: -
IMDG: EMS: F-A, S-B

Limited
Quantities: 5
L

IATA: Cargo:

Maximum
quantity: 60 L

Packaging
instructions:
856
Packaging
instructions:
852

Passengers:

Maximum
quantity: 5 L

Special provision:

A3, A803

	BELLINZONI S.R.L.	Revision nr. 2
	EPOX PREMIUM TRASPARENTE VERTICALE COMPONENTE B	Dated 27/02/2023 Printed on 27/02/2023 Page n. 17/19 Replaced revision:1 (Printed on: 18/01/2021)

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 3

Contained substance

Point 75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage $\geq$ than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

	BELLINZONI S.R.L.	Revision nr. 2
	EPOX PREMIUM TRASPARENTE VERTICALE COMPONENTE B	Dated 27/02/2023 Printed on 27/02/2023 Page n. 18/19 Replaced revision:1 (Printed on: 18/01/2021)

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Acute Tox. 4	Acute toxicity, category 4
STOT RE 2	Specific target organ toxicity - repeated exposure, category 2
Skin Corr. 1A	Skin corrosion, category 1A
Skin Corr. 1	Skin corrosion, category 1
Eye Dam. 1	Serious eye damage, category 1
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
Skin Sens. 1	Skin sensitization, category 1
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic toxicity, category 2
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.
H373	May cause damage to organs through prolonged or repeated exposure.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH205	Contains epoxy constituents. May produce an allergic reaction.
EUH210	Safety data sheet available on request.

Use descriptor system:

LCS	PW	Widespread use by professional workers
PC	1	Adhesives, sealants

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%

	BELLINZONI S.R.L.	Revision nr. 2
	EPOX PREMIUM TRASPARENTE VERTICALE COMPONENTE B	Dated 27/02/2023 Printed on 27/02/2023 Page n. 19/19 Replaced revision:1 (Printed on: 18/01/2021)

- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
 3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
 4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
 13. Regulation (EU) 2017/776 (X Atp. CLP)
 14. Regulation (EU) 2018/669 (XI Atp. CLP)
 15. Regulation (EU) 2019/521 (XII Atp. CLP)
 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
 17. Regulation (EU) 2019/1148
 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
 22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
- The Merck Index. - 10th Edition
 - Handling Chemical Safety
 - INRS - Fiche Toxicologique (toxicological sheet)
 - Patty - Industrial Hygiene and Toxicology
 - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
 - IFA GESTIS website
 - ECHA website
 - Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:

The following sections were modified:

01 / 02 / 03 / 08 / 09 / 10 / 11 / 12 / 14 / 15 / 16.